

# 55513

## TOYOTA T-100

### TOYOTA TACOMA

#### WIRING LOCATION GUIDE

#### GUÍA DE UBICACIÓN DEL CABLEADO

#### IDE D'EMPLACEMENT DES FILS



#### MUST READ FIRST!

All steps must be followed to ensure correct function of the T-Connector. To verify proper installation once installed, test by connecting a test light or properly wired trailer.

#### ¡DEBE LEERSE PRIMERO!

Debe seguirse todos los pasos para asegurar el correcto funcionamiento del Conector-T. Para verificar la correcta instalación, pruebe conectando una luz de prueba o un remolque debidamente cableado.

#### À LIRE D'ABORD!

Pour assurer le bon fonctionnement du T-Connector, il faut suivre toutes les étapes. Pour vérifier que l'installation a été bien effectuée, branchez un feu de test ou une remorque correctement filéée.

3/19/2013

## English

### 1. Toyota Tacoma:

A. Open the tailgate and remove the vehicle's taillights by removing the screws with a 10mm socket (A). Carefully pry the taillights away from the vehicle being careful not to break the alignment tabs.

B. Beginning on the driver's side, locate the vehicle's wiring harness. There will be connection points attached to each taillight matching the ends of the T-Connector (B).

### Toyota T-100:

Locate the vehicle's taillight wiring harness near the rear of the frame. This harness will have connection points on the driver and passenger side of the frame with connectors matching the end of the T-Connector.

2. Separate the connections, taking care not to break the locking tabs. Check to see that the all surfaces are free of dirt. (Clean if necessary.)

3. Beginning on the driver's side, plug the T-Connector end with yellow wire between the wiring connections. Be sure that the T-Connector is fully inserted with locking tabs in place (C).

### 4. Toyota Tacoma:

Route the T-Connector end with the green wire and the 4-flat out through the hole between the vehicle bumper and body (D). Route the green wire to the passenger side up through the hole and insert housing. Be careful to avoid areas that might cut or pinch the wire. Route the 4-flat underneath the bumper to the center of the vehicle.

4. (con't.)

### Toyota T-100:

Route the T-Connector end with the green wire to the passenger side and insert the T-Connector housing with the green wire into the vehicle's corresponding housing.

#### WARNING!

Verify miscellaneous items that may be hidden behind or under any surface before drilling to avoid damage and/or personal injury.

5. Locate a suitable grounding point such as the vehicle's frame or crossmember. Clean dirt and rust proofing from the area. Drill a 3/32" hole and attach the white ground wire using its ring terminal and the screw provided.

6. Mount the converter behind the taillight using the double sided tape provided (E). Secure all loose wires with the cable ties provided.

7. Reinstall all items removed during installation.

**INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-800-798-0813**

