



**EDELBROCK NITROUS SYSTEMS**  
**SUPER VICTOR WITH E3 FOR 8-CYLINDER JET MAP**  
**CATALOG #71852**  
**INSTALLATION INSTRUCTIONS**

Please read both your **DIRECT PORT INSTRUCTION MANUAL** and this **JET MAP** insert before installing your Edelbrock Nitrous System. If you have any questions or comments, please feel free to contact our **Technical Hotline at: 1-800-416-8628** from 7a.m.-5p.m., Monday through Friday, Pacific Time or e-mail us at [Edelbrock@Edelbrock.com](mailto:Edelbrock@Edelbrock.com).

**BILL OF MATERIALS**

Qty.	Description	Qty.	Description
<input type="checkbox"/> 2	Victor Pro Nitrous Solenoid	<input type="checkbox"/> 8	Red Tube Nuts
<input type="checkbox"/> 2	Victor Pro Fuel Solenoid	<input type="checkbox"/> 16	Compression Fittings
<input type="checkbox"/> 8	Edelbrock E3 Nozzles	<input type="checkbox"/> 4	Distribution Blocks
<input type="checkbox"/> 16	3/16" Tubing	<input type="checkbox"/> 2	90° Union Fittings
<input type="checkbox"/> 16	Tube Sleeves	<input type="checkbox"/> 2	6AN Nitrous Filter Fitting
<input type="checkbox"/> 8	Blue Tube Nuts	<input type="checkbox"/> 2	6AN Red Filter Fitting
<input type="checkbox"/> 2	1/8" Male Pipe Nipples	<input type="checkbox"/> 56	Various Jets



**Jet Map**

<u>Approx. HP Gain</u>	<u>Nitrous Jet</u>	<u>Fuel Jet</u>	<u>Sugg. Timing Retard</u>
200 HP	24	20	6°-8°
300 HP	32	28	8°-10°
400 HP	38	34	10°-12°
500 HP	42	38	12°+

This jet map is based on a nitrous system with a flowing fuel pressure of 6.0-6.5 PSI. Any variations different that 6.0-6.5 will change your jet map and potentially damage your engine. We highly recommend using the *Edelbrock Flow Test Tool (Catalog #76506)* to set your flowing fuel pressure.

**Edelbrock Corporation • 2700 California St. • Torrance • CA 90503**  
**Tech Line: 800-416-8628**  
**Office: 310-781-2222**  
**E-Mail: Edelbrock@Edelbrock.com**