

Installation Instructions

Eibach Springs, Inc. • 264 Mariah Circle • Corona, California 92879-1751 • USA • Tech Support 800-222-8811 Ext 114



Adapter Kit # 5.1018K

Kit Contents	Description	Part Number	Qty
	Bearing Cap	UB0038	2
	Flanged Sleeve	UB0037	2

5.1018K must be used when installing caster camber kit with 3510.710 Pro-Street

NOTES: **Read All Instructions Before Beginning Installation**

- Only qualified mechanics experienced in the installation and removal of suspension components should perform this installation.
- Use of a hoist and screw jack is highly recommended and will substantially reduce installation time.
- Never work on or under a vehicle unless it is properly supported by safety stands and wheels are blocked.
- Tire Rotation: In order to increase the life of your tires, it is recommended to rotate your tires every 3,000 miles.
- After installation, it is always important to inspect and adjust the following if necessary:
 - Wheel alignment such as camber, caster & toe.
 - Tire and/or wheel fender clearance.
 - Brake line clearance and attachments.
 - Brake anti-locking and anti-skid system sensors.

Additional Eibach Components Available For Your Car

Eibach Kits	Part Number	Description	Front	Rear
<i>Pro Kit</i>	3510.140	Performance Lowering	1.5"	1.5"
<i>Sportline</i>	4.1035	Extreme Lowering	2.0"	1.8"
<i>Pro Damper</i>	3514.840	Performance Dampers		
<i>Pro Street</i>	3510.710	Street Performance Coil-Over	0-2.5"	0-2.5"
<i>Anti Roll Kit</i>	3518.320	Reduce Body Roll		

Installation of caster camber plate adapter



1. Remove the upper bearing/urethane isolator from the pro street coil over assembly as shown above
2. Remove the urethane isolator and crush sleeve from the upper bearing.



3. Disassemble the upper half of the upper bearing as shown above.



4. Now install the new upper bearing plate onto the lower half from step 3 as shown above.



5. Install the upper bearing assembly back onto the pro street coilovers as shown above.



6. Install the provided spacer on top of the bearing plate as shown above.

