

PART NO. 2117/02117 Black
2117-1 Metallic Ceramic

CAMARO 302-350 - FIREBIRD 305-350 - NOVA 305

THANK YOU FOR MAKING HOOKER HEADERS YOUR CHOICE IN A HIGH PERFORMANCE EXHAUST SYSTEM. EXTENSIVE DYNO/TRACK TESTING HAS ENABLED HOOKER TO OFFER THE MOST ADVANCED DESIGN IN HEADERS FOR YOUR APPLICATION. DUE TO THE RESTRICTED ROOM AVAILABLE IN THE ENGINE COMPARTMENT, YOUR HEADERS MAY BE CLOSE TO SOME BODY AND CHASSIS COMPONENTS. THIS CONDITION IS NORMAL. INSTALLATION, WHILE NOT COMPLEX, MAY BE TIME CONSUMING. HOWEVER, AS SOON AS YOU START YOUR ENGINE, THE ADDITIONAL HORSEPOWER AND IMPROVED PERFORMANCE WILL MORE THAN JUSTIFY YOUR EFFORTS. PROPER INSTALLATION AND MAINTENANCE WILL INSURE LONG LIFE AND MAXIMUM PERFORMANCE FROM YOUR HOOKER HEADERS.

BEFORE STARTING

YOUR VEHICLE MUST BE RAISED A MINIMUM OF 36 INCHES. A FLOOR HOIST IS IDEAL. IF NO HOIST IS AVAILABLE, WE STRONGLY URGE THE USE OF AXLE STANDS AS A SAFETY MEASURE. **CAUTION!** YOUR CAR SHOULD NOT BE SUPPORTED ON A BUMPER JACK.

INSTALLATION PROCEDURE - PLEASE READ CAREFULLY

LEFT SIDE

1. DISCONNECT BATTERY CABLE TO PREVENT DAMAGE TO THE ELECTRICAL SYSTEM.
2. UNBOLT HEADPIPE FROM STOCK EXHAUST MANIFOLD AND PUSH ASIDE.
3. REMOVE OIL FILTER, CLUTCH LINKAGE, SPARK PLUGS, EXHAUST MANIFOLD AND DIPSTICK TUBE. ('76 AND '80 MODELS DO NOT REQUIRE OIL FILTER REMOVAL).
4. STARTING FROM BELOW, WORK HEADER UP AND THROUGH CHASSIS INTO POSITION.
5. PLACE GASKET INTO POSITION AND START ALL BOLTS (MOST RESTRICTED FIRST).
NOTE: VEHICLES EQUIPPED WITH POWER STEERING REQUIRE INSTALLATION OF FURNISHED SPACER. SEE ILLUSTRATION "A".
6. TIGHTEN ALL BOLTS (MOST RESTRICTED FIRST).
7. REINSTALL CLUTCH LINKAGE, OIL FILTER, DIPSTICK TUBE AND SPARK PLUGS.

RIGHT SIDE

1. UNBOLT HEADPIPE FROM STOCK EXHAUST MANIFOLD AND PUSH ASIDE.
2. REMOVE STARTER, SPARK PLUGS AND EXHAUST MANIFOLD.
3. REMOVE THE CENTER BOLT FROM MOTOR MOUNT AND RAISE ENGINE ABOUT 2 INCHES. PLACE A BOARD BETWEEN PAN AND JACK. ('76 AND '80 MODEL DO NOT REQUIRE THAT THE ENGINE BE JACKED UP).
4. STARTING FROM BELOW, WORK HEADER AND STARTER THROUGH CHASSIS AT SAME TIME. ABOUT HALF WAY, INSTALL STARTER.
5. LOWER ENGINE AND REPLACE THE MOTOR MOUNT BOLT.
6. PLACE GASKET INTO POSITION AND START ALL BOLTS (MOST RESTRICTED FIRST).
7. TIGHTEN ALL BOLTS (MOST RESTRICTED FIRST).
8. CONNECT COLLECTORS TO HEADPIPES, USE HOOKER HEADER REDUCER KIT NO. 11030.
NOTE: A DUAL EXHAUST SYSTEM CAN BE FABRICATED USING EITHER HOOKER SUPER COMPETITION TURBO MUFFLERS #21104, #21105 OR #21106; HOOKER COMPETITION TURBOS #21004, #21005 OR #21006; # AND UNIVERSAL TAILPIPE # #16215. HEADER TYPE MUFFLERS DO NOT REQUIRE REDUCERS.
9. CONNECT BATTERY, START ENGINE AND CHECK FOR LEAKS.

WHEN FINISHED, GIVE YOUR CAR A TEST DRIVE CHECKING CAREFULLY FOR ANY NEW NOISES. AFTER SEVERAL DAYS DRIVING, RETIGHTEN ALL BOLTS.

ANY QUESTIONS? PLEASE CONTACT THE CUSTOMER SERVICE DEPARTMENT AT: HOLLEY PERFORMANCE PRODUCTS 704 HWY. 25 SOUTH ABERDEEN, MS 39730 TECHNICAL SERVICE: 270-781-9741 FAX: 270-781-9772 !

Website: www.holley.com

DID YOU KNOW THERE IS MORE TO HOOKER THAN JUST HEADERS? OF COURSE, WE LOVE OUR HOOKER HEADERS, BUT HOOKER BUILDS MORE THAN THE ULTIMATE IN HIGH PERFORMANCE EXHAUST SYSTEMS. ASK YOUR DEALER



WARNING! Breaking in an engine with ceramic-coated headers **WILL** result in damage to the coating and will **VOID** all warranties. Ceramic-coated headers require several heat cycles to fully cure before they will withstand extreme heat. Flowtech® & Hooker® recommend using cast iron exhaust manifolds or old headers to break in new engines to avoid coating damage. Please call tech service at 270-781-9741 for additional information regarding ceramic-coated exhaust products.

LIMITATION OF LIABILITY - DISCLAIMER: THE REGULATION OF EMISSIONS PRODUCTION, NOISE LEVELS AND SAFETY STANDARDS IS UNDERTAKEN BY THE FEDERAL GOVERNMENT, EACH OF THE FIFTY STATE LEGISLATURES AND BY MANY LOCAL MUNICIPALITIES, TOWNS AND COUNTIES.

HOOKER INDUSTRIES MAKES NO WARRANTIES OF MERCHANTABILITY, OF FITNESS FOR PARTICULAR PURPOSE, OR THAT ITS PRODUCTS ARE APPROVED FOR GENERAL USE, OR THAT ITS PRODUCTS COMPLY WITH LAWS, REGULATIONS OR ORDINANCES IN THE STATES WHERE THEY MAY BE SOLD TO THE ULTIMATE PURCHASER, THE CONSUMER.

UNLESS EXPRESSLY STATED TO THE CONTRARY IN THE CATALOG, INSTRUCTION SHEET OR PRICE LIST, THE ENTIRE RISK AS TO THE CONFORMITY OF ANY COMPANY PRODUCT IN ANY SUCH STATE AND AS TO REPAIR SHOULD THE PRODUCT PROVE TO BE DEFECTIVE OR NONCONFORMING, IS ON THE RETAIL PURCHASER, THE BUYER, THE ULTIMATE CONSUMER, OF SUCH PRODUCT AND IT IS NOT UPON THE SELLER, DISTRIBUTOR OR MANUFACTURER.

IN THIS CONNECTION, THE RETAIL PURCHASER, THE BUYER, THE ULTIMATE CONSUMER ASSUMES THE BURDEN OF THE ENTIRE COST OF ANY AND ALL NECESSARY SERVICE, ALTERATIONS OR REPAIR.

THE FOREGOING STATEMENT LIMITS THE LIABILITY OF THE MANUFACTURER.

CALIFORNIA VEHICLE CODE SECTIONS 27156 AND 38391 PROHIBIT THE ADVERTISING, OFFERING FOR SALE, OR INSTALLATION OF ANY DEVICE WHICH MODIFIES A VEHICLE'S EMISSION CONTROL SYSTEM UNLESS EXEMPTED. UNLESS OTHERWISE NOTED, HOOKER HEADERS HAVE NOT RECEIVED AN EXEMPTION FROM THESE CODE SECTIONS AND ARE NOT LEGAL FOR SALE OR USE IN CALIFORNIA ON VEHICLES ORIGINALLY EQUIPPED WITH CATALYTIC CONVERTERS. IT IS ILLEGAL, EXCEPT FOR RACING VEHICLES WHICH MAY NEVER BE DRIVEN UPON A HIGHWAY, TO REMOVE OR OTHERWISE RENDER INOPERATIVE ANY EMISSION CONTROL DEVICE ON REGULATED MOTOR VEHICLES-CHECK CATALOG LISTINGS TO INSURE PROPER APPLICATION. IN THE OTHER 49 STATES, UNLESS OTHERWISE NOTED, HOOKER HEADERS ARE NOT LEGAL FOR POLLUTION CONTROLLED MOTOR VEHICLES, EXCEPT FOR RACING VEHICLES WHICH MAY NEVER BE USED UPON A HIGHWAY AND ARE NOT INTENDED OR APPLICABLE FOR HIGHWAY USE.

