

Wheel Well Guards

7900 - Installation Instructions 2007-13 Chevrolet Silverado/GMC Sierra 1500 2007-14 Chevrolet Silverado/GMC Sierra 2500/3500

PACKAGE CONTENTS:



TOOLS REQUIRED:

- **Phillips Head Screwdriver**
- Drill Motor & 1/8" Drill Bit (For GMC Sierra only)

VEHICLE PREPARATION:

Your vehicle's rear fender wells should be cleaned prior to the installation of your new Wheel Well Guards.



Installation

Read all directions thoroughly prior to the installation of your Wheel Well Guards.

A, B, C & D are pre-drilled fastener locations for installation.



- 1. Verify that you are installing the correct Wheel Well Guard by checking the part no. located on the backside of the part.
- 7900 DS installs on the driver's side.
- 7900 PS installs on the passenger's side.



- 2. Install 2 U-Clips over the Wheel Well Guard's pre-drilled holes at locations B & C.
- NOTE: The U-Clips need to be installed over the Wheel Well Guard lip with the threaded side of the U-Clip up.

3. Insert the Wheel Well Guard into the rear wheel well opening over the tire.

NOTE: It is not necessary to remove the tire.

4. Push The Wheel Well Guard up into the wheel well opening.

5. Insert the lower flap sections of the Wheel Well Guard into the fender well behind the fender well lip. Perform this step for both the front and rear lower flap sections.



6. Tuck the remaining portion of the Wheel Well Guard behind the fender lip all the way around the fenderwell opening.

7. Align the U-Clip holes with the factory fender holes at locations B & C. Install #10 SEM screws under the fender well lip, through the fender sheet metal and into the U-Clips at location's B & C. Leave screws loose until all fasteners are installed.

8.Install #10 SEM screws at locations A & D through the Wheel Well Guard, through the fender sheet metal and into U-Clips (see below).

- Do not clip the U-clip over the sheet metal. The U-Clip functions as a "nut" and is placed on the backside of the sheet metal.
- NOTE: FOR GMC SIERRA ONLY: Prior to installing fasteners you must drill 1/8" holes through the sheet metal at locations A & D. Use the pre-drilled fastener locations A & D as a template. Drill 1/8" holes and install #10 SEM screws.



- 9. Once all fasteners at locations A, B, C, & D are installed, tighten with a Phillips head screwdriver.
- 10. Finish by tightening all fasteners.
- Repeat steps 1-10 for the other side of the vehicle.

Congratulations, you have now successfully installed your new Husky Liners Wheel Well Guards. If you have any questions please call us at 1-800-344-8759.

HUSKY LINERS WHEEL WELL GUARDS LIMITED LIFETIME WARRANTY

WINFIELD CONSUMER PRODUCTS WARRANTS YOUR HUSKY LINERS WHEEL WELL GUARD PROTECTION PRODUCT WITH A LIMITED LIFETIME WARRANTY TO THE ORIGINAL PURCHASER. IF YOUR FINISHED PRODUCT IS FOUND DEFECTIVE, WINFIELD CONSUMER PRODUCTS WILL AUTHORIZE THE REPLACEMENT OF YOUR PRODUCT AT NO CHARGE TO THE ORIGINAL PURCHASER. THIS WARRANTY COVERS PRODUCT REPLACEMENT ONLY. WINFIELD CONSUMER PRODUCTS WILL NOT PROVIDE A MONETARY REFUND FOR THE PRICE OF THE PRODUCT OR CHARGES INCURRED DURING INSTALLATION. THIS WARRANTY IS NOT TRANSFERABLE. WIN-FIELD CONSUMER PRODUCTS ASSUMES NO LIABILITY FOR PRODUCT FAILURE DUE TO ACCIDENT, COLLISION, NEGLIGENCE, VANDALISM OR ABUSE.

THERE IS NO WARRANTY OF MERCHANTABILITY AND NO WARRANTY THAT THE PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE OR USE. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS AND YOU MAY HAVE OTHER RIGHTS WHICH VARY FROM JURISDICTION.

THIS PRODUCT IS TO BE USED IN COMPLIANCE WITH ALL APPLICABLE STATE OR PROVINCIAL LAWS. INSTALLATION OF THIS PRODUCT IN A MANNER THAT VIOLATES STATE OR PROVINCIAL LAW IS A MISUSE OF THE PRODUCT AND VOIDS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANT-ABILITY. WINFIELD CONSUMER PRODUCTS SHALL NOT BE LIABLE IN ANY MANNER WHATSOEVER FOR DAMAGES RELATED TO THE USE OF THIS PRODUCT IN AN ILLEGAL MANNER.

FOR WARRANTY SERVICE CONTACT YOUR HUSKY LINERS DEALER OR CALL WINFIELD CONSUMER PRODUCTS AT (800) 344-8759.