


Continued

INSTALLATION INSTRUCTIONS



10. Assemble the saddle and "L" bracket using the hardware provided.



11. Install the trim seal onto the heat shield as shown.



12. Attach the saddle bracket assembly to the heat shield using the hardware provided.

NOTE: Do not tighten completely at this time.



13. Attach the rubber mounted studs to the "Z" bracket using the hardware provided.



14. Loosen and remove the bolt that retains the transmission hanger to the transmission.



15. Attach the "Z" bracket to the transmission hanger using the bolt removed in the previous step.




16. Attach the heat shield to the rubber mounted studs on the "Z" bracket using the hardware provided.

NOTES: Do not tighten completely at this time.



17. Attach the silicone hose to the throttle body using the hose clamp provided.



18. Install the K&N® intake tube, feeding the straight end through the hole in the heat shield.

19. Install the radius end of the intake tube into the silicone hose at the throttle body and tighten the hose clamp.



20. Secure the saddle bracket to the intake tube using the hose clamp provided.



21. Insert the crankcase vent hardline into the grommet in the K&N® intake tube.



22. Install the adapter onto the K&N® intake tube.



23. Install the Filtercharger element and tighten hose clamp.

24. Reconnect the air temperature sensor electrical connection.

25. Reconnect the vehicle's negative battery cable. Double check to make sure everything is tight and properly positioned before starting the vehicle.

26. The C.A.R.B. exemption sticker, (attached), must be visible under the hood so that an emissions inspector can see it when the vehicle is required to be tested for emissions. California requires testing every two years, other states may vary.

27. It will be necessary for all K&N® high flow intake systems to be checked periodically for realignment, clearance and tightening of all connections. Failure to follow the above instructions or proper maintenance may void warranty.

ROAD TESTING:

1. Start the engine with the transmission in neutral or park, and the parking brake engaged. Listen for air leaks or odd noises. For air leaks secure hoses and connections. For odd noises, find cause and repair before proceeding. This kit will function identically to the factory system except for being louder and much more responsive.

2. Test drive the vehicle. Listen for odd noises or rattles and fix as necessary.

3. If road test is fine, you can now enjoy the added power and performance from your kit.

4. K&N Engineering, Inc., requires cleaning the intake system's air filter element every 100,000 miles. When used in dusty or off-road environments, our filters will require cleaning more often. We recommend that you visually inspect your filter once every 25,000 miles to determine if the screen is still visible. When the screen is no longer visible some place on the filter element, it is time to clean it. To clean and re-oil, purchase our filter Recharger® service kit, part number 99-5050 or 99-5000 and follow the easy instructions.

**50-STATE STREET LEGAL
CARB EXEMPT**



* FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal *

• 1455 CITRUS ST., P.O. BOX 1329, RIVERSIDE, CA., U.S.A. 92502 • TECH SERVICE 800-858-3333 • FAX 951-826-4001

• e-mail: tech@knfilters.com • WWW: <http://www.knfilters.com>

17166C

1/24/13