



INSTALLATION INSTRUCTIONS

11" X-Stream Custom Assemblies

Congratulations, you have purchased the finest air intake kit that money can buy. The following procedure **MUST** be followed to ensure proper performance and seal of the K&N X-Stream Custom Assembly. Failure to follow any of these steps **CAN** result in the X-Stream's top warranty becoming void

CAUTION: It is imperative that no part of the X-Stream® top comes into contact with anything on the vehicle at any time. If the X-Stream® top rubs against anything it might become irreparably damaged. Double check measurements to verify that no interference will occur **BEFORE** closing the hood.

Step 1 Thread the all-thread stud into the carburetor until it bottoms out.
Secure with jam nut.

NOTE: If your carburetor has a 5/16" x 18" stud boss, use the provided 5/16 to 1/4" adapter.

Step 2 Install the neoprene gasket and the base plate on carburetor.

Step 3 Install the K&N Filtercharger making sure it is fully seated in base.

Step 4 Thread one of the nylock nuts onto stud.

Step 5 Place a straight edge across the top of the Filtercharger element.
Adjust the nylock until the top of it is even with the bottom of the straight edge.

Step 6 Remove the stud and cut it 1-1/4" above the nylock. De-burr the end of the stud and make sure the nut threads on smoothly.

Step 7 Re-install the stud making sure the nylock is still even with the top of the element.

Step 8 Place one of the steel washers on the stud.

Step 9 Install the X-Stream Air Flow Top making sure it is fully seated on the Filtercharger all the way around.

Step 10 Install rubber washer.

Step 11 Install steel washer.

Step 12 Install nylock nut - It should become tight 1-1/2 to 2 turns after contacting the flat washer.

