



**INSTALLATION INSTRUCTIONS
EXTENDED OIL PUMP PICKUPS
P/N 24700, 24750, 24760, 24766, 24800**

These pickups are to be used with Moroso Oil Pan Numbers:

19570, 20710, 20730	Use 24700 Pickup
19580, 20760 Wedge Engines	Use 24750 Pickup
19580, 20760 Hemi Engines	Use 24800 Pickup
20765	Use 24760 Pickup
20766 Pan	Use 24766 Pickup

All of these pickups have a pipe thread on one end which screws into the stock oil pump or block. The pickup must screw in a minimum of (4) threads for proper retention. Due to manufacturing tolerances, it may be necessary to increase the thread in the oil pump or block. Use a 3/8" NPT tap, (1/2-NPT tap for 426 Hemi), and increase the thread the required amount. Be absolutely sure to clean out any debris created from tapping the hole. To prevent leakage around these threads, we highly recommend the use of Loctite to secure the pickup in place.

PARTS LIST USED ONLY ON P/N 24700

- 1 Oil Pump Pickup, Clear Zinc
- 1 Washer F M .509ID .870OD .120T
- 1 Nut, 3/8-24 Serrated Face, Grade 5
- 1 Spacer, .87 IN. OD x .50 IN L x .19 IN W
- 1 Nut, 1/2-20 HH Blk Ox Grade 8
- 1 Stud, 1/2-20 & 3/8-24Mult. Threads

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC

80 CARTER DR • GUILFORD, CT 06437

Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moroso.com