



Ford C4 Transmission Pan P/N 42040

Important Installation Note

This Transmission Pan must be used with any of the following filters: Ford p/n D4FZ7A098A, ATP p/n 1-4945, or Fram p/n FT1035.

1. Drain fluid and remove old pan. Clean any old gasket material from the pan-mounting surface on the transmission. Remove the old filter and replace with a new one listed above.
2. Install the supplied Mounting Studs into the transmission, place a new gasket on the pan rail, tighten the pan with supplied Serrated Nuts to 10 ft-lbs. (NOTE: Moroso does not recommend using any type of sealer on the gasket. Small pieces may dislodge and clog the transmission or transbrake internals resulting in failure).
3. Check that the drain plugs are tight. Fill the trans with fresh fluid to the proper level on the dipstick.

*For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 8:30am – 5:00pm Eastern Time*

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • P.O. Box 1470 • GUILFORD, CT 06437
Phone: (203) 453-6571 • FAX (203) 453-6906

Rev.A
120800

Visit Us At www.moroso.com

42040INST



Ford C4 Transmission Pan P/N 42040

Important Installation Note

This Transmission Pan must be used with any of the following filters: Ford p/n D4FZ7A098A, ATP p/n 1-4945, or Fram p/n FT1035.

1. Drain fluid and remove old pan. Clean any old gasket material from the pan-mounting surface on the transmission. Remove the old filter and replace with a new one listed above.
2. Install the supplied Mounting Studs into the transmission, place a new gasket on the pan rail, tighten the pan with supplied Serrated Nuts to 10 ft-lbs. (NOTE: Moroso does not recommend using any type of sealer on the gasket. Small pieces may dislodge and clog the transmission or transbrake internals resulting in failure).
3. Check that the drain plugs are tight. Fill the trans with fresh fluid to the proper level on the dipstick.

*For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 8:30am – 5:00pm Eastern Time*

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • P.O. Box 1470 • GUILFORD, CT 06437
Phone: (203) 453-6571 • FAX (203) 453-6906

Rev.A
120800

Visit Us At www.moroso.com

42040INST



Ford C4 Transmission Pan P/N 42040

Important Installation Note

This Transmission Pan must be used with any of the following filters: Ford p/n D4FZ7A098A, ATP p/n 1-4945, or Fram p/n FT1035.

1. Drain fluid and remove old pan. Clean any old gasket material from the pan-mounting surface on the transmission. Remove the old filter and replace with a new one listed above.
2. Install the supplied Mounting Studs into the transmission, place a new gasket on the pan rail, tighten the pan with supplied Serrated Nuts to 10 ft-lbs. (NOTE: Moroso does not recommend using any type of sealer on the gasket. Small pieces may dislodge and clog the transmission or transbrake internals resulting in failure).
3. Check that the drain plugs are tight. Fill the trans with fresh fluid to the proper level on the dipstick.

*For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 8:30am – 5:00pm Eastern Time*

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • P.O. Box 1470 • GUILFORD, CT 06437
Phone: (203) 453-6571 • FAX (203) 453-6906

Rev.A
120800

Visit Us At www.moroso.com

42040INST



Ford C4 Transmission Pan P/N 42040

Important Installation Note

This Transmission Pan must be used with any of the following filters: Ford p/n D4FZ7A098A, ATP p/n 1-4945, or Fram p/n FT1035.

1. Drain fluid and remove old pan. Clean any old gasket material from the pan-mounting surface on the transmission. Remove the old filter and replace with a new one listed above.
2. Install the supplied Mounting Studs into the transmission, place a new gasket on the pan rail, tighten the pan with supplied Serrated Nuts to 10 ft-lbs. (NOTE: Moroso does not recommend using any type of sealer on the gasket. Small pieces may dislodge and clog the transmission or transbrake internals resulting in failure).
3. Check that the drain plugs are tight. Fill the trans with fresh fluid to the proper level on the dipstick.

*For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 8:30am – 5:00pm Eastern Time*

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • P.O. Box 1470 • GUILFORD, CT 06437
Phone: (203) 453-6571 • FAX (203) 453-6906

Rev.A
120800

Visit Us At www.moroso.com

42040INST