



**CHEVY ELECTRIC WATER PUMPS  
P/N's 63547 & 63557**

**INSTALLATION INSTRUCTIONS**

These instructions are a basic guideline for installing a Moroso Performance Electric Water Pump. Always consult the proper manufacturer service manual for your vehicle for any general assembly/disassembly information.

This Electric Water Pump was designed to fit in the stock location on the engine. Check and clean all new pieces for any debris that may prevent the gaskets from sealing. When installing, make sure the gasket sealing area on the engine is cleaned of any old sealing material. Use a high quality gasket sealer and the supplied hardware and gaskets to prevent leaks. Place two gaskets on the back of the water pump, the two spacers, the other two gaskets, and bolt the complete assembly to the engine block.

The stock bypass and/or heater hose to the Water Pump are not used, and should be blocked off. The stock accessories (power steering pump, alternator, etc.) may have to be relocated in some cases to ensure clearance between belts, hoses, etc. The accessory drive belt no longer turns the water pump. In applications where the water pump belt drives other accessories, a shorter drive belt will have to be used to bypass the water pump drive. On serpentine belt drive systems the tension/idler pulley may have to be re-located.

**CAUTION: Seal failure will occur if pump is operated without water or coolant in the system or the pump.**

Incorrect wiring of this pump will cause damage to the pump motor and/or your engine. The Red Wire is Positive and should be connected to a 12 Volt, 20 Amp fused source. The Black Wire is Negative and should be connected to a suitable ground such as the engine or chassis.

***For Technical Assistance, Call Moroso's Tech Line at  
(203) 458-0542, 8:30am – 5:00pm Eastern Time***

**MOROSO PERFORMANCE PRODUCTS, INC  
80 CARTER DR • GUILFORD, CT 06437  
Phone: (203) 453-6571 • FAX (203) 453-6906**

**Visit Us At [www.moroso.com](http://www.moroso.com)**



**CHEVY ELECTRIC WATER PUMPS  
P/N's 63547 & 63557**

**INSTALLATION INSTRUCTIONS**

These instructions are a basic guideline for installing a Moroso Performance Electric Water Pump. Always consult the proper manufacturer service manual for your vehicle for any general assembly/disassembly information.

This Electric Water Pump was designed to fit in the stock location on the engine. Check and clean all new pieces for any debris that may prevent the gaskets from sealing. When installing, make sure the gasket sealing area on the engine is cleaned of any old sealing material. Use a high quality gasket sealer and the supplied hardware and gaskets to prevent leaks. Place two gaskets on the back of the water pump, the two spacers, the other two gaskets, and bolt the complete assembly to the engine block.

The stock bypass and/or heater hose to the Water Pump are not used, and should be blocked off. The stock accessories (power steering pump, alternator, etc.) may have to be relocated in some cases to ensure clearance between belts, hoses, etc. The accessory drive belt no longer turns the water pump. In applications where the water pump belt drives other accessories, a shorter drive belt will have to be used to bypass the water pump drive. On serpentine belt drive systems the tension/idler pulley may have to be re-located.

**CAUTION: Seal failure will occur if pump is operated without water or coolant in the system or the pump.**

Incorrect wiring of this pump will cause damage to the pump motor and/or your engine. The Red Wire is Positive and should be connected to a 12 Volt, 20 Amp fused source. The Black Wire is Negative and should be connected to a suitable ground such as the engine or chassis.

***For Technical Assistance, Call Moroso's Tech Line at  
(203) 458-0542, 8:30am – 5:00pm Eastern Time***

**MOROSO PERFORMANCE PRODUCTS, INC  
80 CARTER DR • GUILFORD, CT 06437  
Phone: (203) 453-6571 • FAX (203) 453-6906**

**Visit Us At [www.moroso.com](http://www.moroso.com)**