


INSTALLATION INSTRUCTIONS


APPLICATION: STEP BAR / 88-98 CHEVY/GMC C/K Pickup, 92-94 CHEVY Blazer Fullsize, 95-99 CHEVY Tahoe - 2 door, 92-99 GMC Yukon - 2 door - Regular Cab APP# 23-0500, 23-0505, 25-0500, 25-0505, 25-0630, 25-0635 25-0885, 25-0890, 26-0500, 26-0505, 26-0630, 26-0890

ITEM	QUANTITY	DESCRIPTION	TOOLS NEEDED
1	2	STEP BAR ASSEMBLY	19MM SOCKET
2	2	FRONT MOUNTING BRACKETS	19MM WRENCH
3	2	REAR MOUNTING BRACKETS	TORQUE WRENCH
4	4	M12 LONG HEX HEAD BOLTS	
5	4	1/2" SHORT HEX HEAD BOLTS	
6	8	1/2" FLAT WASHER	
7	8	1/2" LOCK WASHER	

ANTI-SEIZE LUBRICANT MUST BE USED ON ALL STAINLESS STEEL FASTENERS TO PREVENT THREAD DAMAGE AND GALLING

- 1. Remove all contents from box, verify all parts listed are present and free from damage. Carefully read and understand all instructions before attempting installation.
- 2. Attach brackets to vehicle body mounts using metric bolts as shown.
- 3. Attach step bar to bracket using 1/2" fasteners. NOTE: Use correct hole location for the rear leg of step bar for your vehicle. Tube should not touch vehicle body.
- 4. Make sure step bar and brackets are properly aligned with vehicle and tighten fasteners. Recommended torque value 50-55 ft-lbs. for 12mm bolts and 64 ft-lbs. for 1/2" fasteners.





CARE INSTRUCTIONS

- REGULAR WAXING IS RECOMMENDED. DO NOT USE ANY TYPE OF POLISH OR WAX THAT MAY CONTAIN ABRASIVES.
- STAINLESS STEEL PRODUCTS CAN BE CLEANED WITH MILD SOAP AND WATER. STAINLESS STEEL POLISH SHOULD BE USED TO POLISH SMALL SCRATCHES.
- GLOSS BLACK FINISHES SHOULD BE CLEANED WITH MILD SOAP AND WATER.

