



BEDCAPS/ TAIL GATE COVERS

PLEASE READ THESE INSTRUCTIONS BEFORE INSTALLATION. BECAUSE OF THE TYPE OF ATTACHMENT METHOD USED ON THE BEDCAP IT IS IMPORTANT TO READ INSTRUCTIONS FULLY BEFORE FITTING. **IT IS ALSO EASIER TO INSTALL WITH THE HELP OF A FRIEND.**

THE DOUBLE SIDED TAPE ADHERES AND CURES BEST AT TEMPERATURES ABOVE 65 DEGREES (F). IF THE BEDCAP IS BEING FITTED BELOW 65 DEGREES IT IS ADVISABLE TO "WARM" THE CONTACT AREA OF THE VEHICLE (A HOT AIR GUN OR HAIR DRYER MAY BE USED).

- 1- **BEFORE REMOVING RED BACKING FROM TAPE,** TRIAL FIT THE BEDCAP. TAKE NOTE OF PROPER FIT AND CENTER THE STAKE POCKET HOLES (IF APPLICABLE).
- 2- REMOVE BEDCAP AND WITH THE ALCOHOL PREP-PAD PROVIDED THOROUGHLY CLEAN THE CONTACT AREA WHERE TAPE WILL ADHERE (CLEAN YOUR VEHICLE BEFOREHAND, TO MAKE SURE IT IS FREE OF DIRT, GREASE, OR WAX).
- 3- REMOVE RED BACKING FROM TAPE AND, STARTING AT THE REAR OF THE VEHICLE, SLOWLY PLACE BEDCAP IN POSITION.
- 4- APPLY PRESSURE TO TOP OF BEDCAP TO INSURE THAT ALL TAPE IS PROPERLY SEATED.
- 5- **THE ADHESIVE REQUIRES 48 HOURS TO FULLY CURE.** AVOID GETTING VEHICLE WET UNTIL 48 HOURS AFTER INSTALLATION.

Installation Tip: If you are using the Wade Bedcap with a tonneau cover, camper shell or tie-downs, it is important to allow for the expansion and contraction of the Bedcap in various temperatures. It is advisable to install the various items so they are snug against the Bedcap **WITHOUT** over tightening. **OR**, if you feel it isn't tight enough, you can cut a gap in the Bedcap of at least a half an inch on either side of the clamp. Failure to do so will result in the warping of the product which will not be covered by the warranty.

Porfavor lea estas instrucciones antes de la instalación. Es muy importante leer las istrucciones **completamente** para instalar el BEDCAP apropiadamente. Tambien será mas fácil instalarlo con la ayuda de un amigo.

La cinta adhesiva pega y cúre mejor a temperaturas sobre 65 grados (F). Si esté instalando el BEDCAP en temperaturas menos de 65 grados, se debe calentar la area de contacto en el vehículo con aire caliente (usando un secador de pelo por ejemplo).

1. Antes de quitar el forro rojo de la cinta, practica el intalamiento y tome nota del apto correcto, asegurese de que los agujeros esten en el centro (si se aplica).
2. Remueve el BEDCAP, y sabiendo las areas de contaco en el vehículo, limpialas bien con el paquete de alcohol proveido.
3. Remueve el forro rojo de la cinta y, empesando al trás del vehículo, ponelo lentamente en la posición correcta.
4. Pone presión sobre el BEDCAP para asegurar que toda la cinta este bien pegado.
5. El adhesivo requiere 48 horas para curar completamente. Se debe evitar mojado el vehiculo por 48 horas despues de la instalación del BEDCAP.