



Tru Boost External Sensor Kit PN 30-4351

The 30-4351 Kit Contains:

- (1) Pressure sensor
- (1) Cable, External Sensor
- (1) Adapter, 1/8 NPT Female to -4 Male
- (1) Adapter, 1/8 NPT Female to 3/16 Barb



External Pressure Sensor

The Tru Boost is capable of reading boost levels up to 50 psig when using the external sensor. To use the external sensor, connect the pressure sensor to manifold pressure using the supplied adapters. Connect the black plug on the harness to the mating plug on the end of the sensor. Plug the single row 3-pin connector into the mating 3-pin connector on the back of the gauge. In order for the Tru Boost to read the external sensor, the external sensor (E) must be selected in the pressure sensor (SEn) option. To enter the program menu, hold both buttons down for 2 seconds. The gauge will display "PRG". Hold both buttons again for 2 seconds to move to the first option. Push both buttons at the same time to move to the next option. When the sensor option (SEn) is shown, select the external pressure sensor (E) by pressing either button. Continue scrolling through the options by pressing both buttons until the run mode is reached. The Tru Boost is now configured to read the external pressure sensor.

Note: With the external sensor selected, the LED lights will flash red and the center digits will display "ErP" if the external sensor is shorted or disconnected.

AEM Electronics warranty

Advanced Engine Management Inc. warrants to the consumer that all AEM High Performance products will be free from defects in material and workmanship for a period of twelve (12) months from date of the original purchase. Products that fail within this 12-month warranty period will be repaired or replaced at AEM's option, when determined by AEM that the product failed due to defects in material or workmanship. This warranty is limited to the repair or replacement of the AEM part. In no event shall this warranty exceed the original purchase price of the AEM part nor shall AEM be responsible for special, incidental or consequential damages or cost incurred due to the failure of this product. Warranty claims to AEM must be transportation prepaid and accompanied with dated proof of purchase. This warranty applies only to the original purchaser of product and is non-transferable. All implied warranties shall be limited in duration to the said 12-month warranty period. Improper use or installation, accident, abuse, unauthorized repairs or alterations voids this warranty. AEM disclaims any liability for consequential damages due to breach of any written or implied warranty on all products manufactured by AEM. Warranty returns will only be accepted by AEM when accompanied by a valid Return Merchandise Authorization (RMA number. Product must be received by AEM within 30 days of the date the RMA is issued.

Please note that before AEM can issue an RMA for any electronic product, it is first necessary for the installer or end user to contact the EMS tech line at 1-800-423-0046 to discuss the problem. Most issues can be resolved over the phone. Under no circumstances should a system be returned or a RMA requested before the above process transpires.

AEM will not be responsible for electronic products that are installed incorrectly, installed in a non approved application, misused, or tampered with.

Any AEM electronics product can be returned for repair if it is out of the warranty period. There is a minimum charge of \$50.00 for inspection and diagnosis of AEM electronic parts. Parts used in the repair of AEM electronic components will be extra. AEM will provide an estimate of repairs and receive written or electronic authorization before repairs are made to the product.

ADVANCED ENGINE MANAGEMENT INC.

This product is legal in California for racing vehicles only and should never be used on public highways.
Advanced Engine Management, 2205 126th Street Unit A Hawthorne, CA. 90250, Phone: (310) 484-2322 Fax: (310) 484-0152
Instruction Part Number: 10-4351, © 2006 Advanced Engine Management, Inc.