



Lansdale, PA 19446

Please save your warranty statement and mail in the completed warranty registration form below.

55035 Rev 1

**10 YEAR LIMITED WARRANTY
(US AND CANADA ONLY)**

Budge Industries, LLC. with its principle place of business at 1690 Sumneytown Pike, Suite 250, Lansdale, PA 19446, warrants to the original purchaser that it will correct any defects in material or workmanship by repair or replacement of this car cover.

To have this warranty honored, the original purchaser should return the car cover, postage paid, along with a copy of the receipt, to Budge Industries LLC., 840 4th Street, Henderson, KY 42420. The repaired or replaced cover will be returned to the sender with-in 45 days of its receipt.

THE EXPRESS WARRANTY SET FORTH ABOVE IS THE ONLY WARRANTY APPLICABLE TO THE PRODUCT AND IS EXPRESSLY IN LIEU OF ANY OTHER WARRANTY, EXPRESSED OR IMPLIED WARRANTY OF MERCHANTABILITY OF FITNESS FOR A PARTICULAR PURPOSE.

Please send _____ Security Cable Lock Kits at a cost of \$10.95 each plus \$2.00 each for shipping and handling to: (UPS cannot ship to P. O. Box)

NAME _____

ADDRESS _____

CITY _____ STATE _____ ZIP _____

Kentucky and Pennsylvania Residents -- please include 6% state sales tax.

**ORDER FORM
SECURITY CABLE LOCK KIT**

BUDGE SECURITY LOCK KIT,
will help keep your cover secure and help prevent unwanted removal

**MAKE CHECK OR MONEY ORDER PAYABLE TO
BUDGE INDUSTRIES, LLC.
AND SEND TO THE ADDRESS BELOW:**



www.BudgeIndustries.com
Budge Industries, LLC.
ATTN: Cable Lock Order
1690 Sumneytown Pike, Suite 250
Lansdale, PA 19446

Please allow 4-6 weeks for delivery

WARRANTY REGISTRATION CARD

Please fill out and mail this card to validate your limited 10 year warranty, within US & Canada only, within ten days of purchase. (Please print) or register on-line at www.budgeindustries.com

Name _____

Address _____

City _____ State _____ Zip _____

Phone (_____) _____

Email: _____

Date of Purchase _____ Where Purchased _____

Car Cover Style or Part # _____ Year and Make of Car _____

Care Instructions

To clean your car cover, we suggest diluting a mild liquid detergent in cold or warm water, then lightly cleanse with sponge. If hand washing your cover, we suggest you install it on your car.

OR

Wash in front load double/triple commercial washer, in cold water with 1/4 cup of mild liquid laundry detergent. **RINSE THOROUGHLY.** Line or air dry your car cover. **NEVER PLACE YOUR COVER IN A DRYER!!!**

WARNINGS!

PLEASE READ PRIOR TO USE OF THIS COVER!

- **NOT LIABLE FOR REPAINTED SURFACES OR LACQUER PAINT.** Repainted vehicles should not be covered for a minimum of 6 months. It is best to check with your painter or body shop for recommended "cure" time. Use of any cover on a repainted vehicle may cause damage which is not due to the cover, but due to the new paint.
- For maximum performance do not cover a wet vehicle.
- Caution: **NEVER** cover a hot tail pipe.
- **NEVER cover a car with convertible top down, windows or sunroof open or t-tops out, or while trailering a vehicle, as this cover will NOT prevent water from penetrating your vehicle.**

Weather Conditions:

High Winds: If you are located in a high wind area be sure to tie down your cover using the grommets provided. Do not rely solely on the elasticized bottom of your cover to provide maximum protection from strong wind. Your cover blowing away is NOT covered under the warranty.

Freezing Weather: In unusual circumstances, a layer of ice may form between your vehicle and this cover. **This layer of ice must be thawed before removing your cover.** You may expedite the thawing process by pouring warm water over the cover and gently lifting the cover as the ice begins to melt. If any resistance occurs, repeat process.

Please save the warranty statement and mail in the completed warranty registration form (see reverse) to:

Budge Industries, LLC.
ATTN: Warranty Registration
1690 Sumneytown Pike, Suite 250
Lansdale, PA 19446



THE ORIGINAL CAR COVER COMPANY

The **RAIN BARRIER™**
SEMI-CUSTOM® CAR COVER

WATER PROOF
LIMITED TEN YEAR WARRANTY
United States and Canada Only
Enjoy your car cover!

Your cover is made from waterproof material. This is a three-layer material, which consists of an inside and outside layer of spun-bond with a layer of waterproof film in the center.

This cover has been designed to provide superior resistance to the sun, rain, dirt, dust, tree sap, bird droppings, and other pollutants.

Your cover is unique because it is waterproof, yet completely breathable. All covers can cause condensation to appear under the cover when the air is warmer under the cover than outside the cover. The advantage of your cover is that it allows trapped moisture to "breathe" back through the material and evaporate. Trapped moisture can damage vehicle paint. Never cover a vehicle that already has a wet surface. **Never cover a car with the convertible top down or T tops out or windows open.**

INSTALLATION AND CARE INSTRUCTION:

Identify the front and rear of your cover. One end of your cover has been marked "FRONT" for proper fit. You can clearly identify the rear of the cover by locating the attached loop sewn on the back center of the cover.

Elastic, sewn at the bottom of the cover, will hold your cover in place under normal conditions; do not rely on the elastic, utilize the grommets to tie down your cover.

To install the cover, find the loop sewn to the back of the cover. Place the loop around the license plate, or any other object protruding from the rear of your vehicle or open trunk and place the loop inside the trunk which you should then close to secure. Simply cover your vehicle from back to front, securing firmly and evenly over the front and rear bumpers. Please secure your cover using a rope and tie down grommets, as we are not responsible if your cover blows away or is stolen.

An antenna patch has been included with the cover for non-retractable antennas. Simply cover your vehicle and mark where the antenna hits the cover. Apply the adhesive-backed antenna patch to the spot, and punch a hole in the center of the patch.

Removing your car cover: release both ends and fold toward the middle of the car, using a fold approximately twelve inches wide. Fold the cover three times at the center of the car. Use of this procedure will allow you to cover your car in just a few moments time.