



NHRA accepted, Collector Tethers meet the 2014 NHRA rule requirement for tethering removable slip on header collectors. 100% Stainless Steel Construction.



Assembly Instructions

1. Remove the nylocks on clamps, discard and replace with included high temp stainless lock nuts. Although all Collector Tethers include high temperature, non galling lock nuts, we recommend a slight amount of anti seize compound on the t-bolt threads prior to installing the lock nuts.
2. Install collector clamps in preferred locations. Merge style will need to be located at the throat.
3. Install primary clamps on preferred tubes.
4. Slide the cables over the t-bolt on both clamps prior to placing the trunnion on the t-bolt. Keep the tether ends towards the trunnion / nut side of the clamps. Apply anti seize and install the provided high temp lock nuts.
5. Adjust the primary clamp so the tether is slightly draped and not taunt. The tether should have a slight amount of drape to it as it is not designed to be a primary retention device.
Once your Collector Tethers are adjusted to your liking, tighten the lock nuts.

Due to the intended use, all Collector Tether products are sold without any implied warranty of any kind. The buyer assumes all risk as to quality, performance and use of these products and agrees to hold Collector Tethers, and their agents and employees harmless for any injury, loss, or damage; including any and all incidental or consequential damages arising from the sale, installation, or use.



www.CollectorTethers.com

CollectorTethers@gmail.com