



## INSTALLATION INSTRUCTIONS

1075 North Ave. Sanger, CA 93657-3539 local: 559-875-0222 fax: 559-876-2259 toll free: 800-445-3767

### STREET PERFORMANCE & NITRO DROP 2 SHOCKS

**Congratulations! You were selective enough to choose a BELLTECH PRODUCT.**

Belltech Shocks for truck suspensions are designed for easy installation. If not otherwise stipulated in these instructions, all suspension components are installed and removed in accordance with the manufacturer's specifications for installing and removing standard damper components.

#### Construction Lube

When you install your Belltech Street Performance or Nitro Drop 2 Shock you may notice a slight oil drip down the side. **The shock is not leaking.** This is oil lubrication used in the construction assembly of the shock. Simply wipe the oil off with a damp cloth.


#### Nitro Drop 2 Shocks

Your Nitro Drop 2 Shock is a low pressure oil shock. If the shock is compressed the rod will not return to an extended position on its own. ***The shock's performance relies on the internal Belltech valving technology which is not affected by the relative pressure of the shock.***

#### Pin Bushings

Your Belltech Street Performance or Nitro Drop 2 Shocks may be fitted with a Pin Bushing. If so it is necessary to properly fit the bushing to your vehicle by choosing the correct notch on the Pin Bushing.

1. Remove OE shock from vehicle.
2. Examine OE pin bushing and measure diameter of notch.
3. Compare to the 2 different notch sizes on the top and bottom of the supplied Belltech Pin Bushing and use the notch that most closely matches your OE pin bushing.



4. Install the shock with the selected notch sandwiching the shock mount of the vehicle.

## **Dust Cover**

Your Belltech Street Performance Shocks may be fitted with a removable dust cover. Some vehicle applications may require you to remove the dust cover for more clearance.



1. Check vehicle to see if there is enough clearance for dust cover. If there is not enough clearance, remove the dust cover by removing the pin bushings and washers and then remove the dust cover.
2. Install included 10mm (0.39in), part number 112445, dust cover spacer.



3. Install washer and bottom pin bushing, with selected notch facing up (see Pin Bushing section, above), then install on vehicle with top pin bushing, with selected notch facing down (see Pin Bushing section, above) and washer.