RV Suspension

LP 25 and LP 35 Series

This Hellwig Helper Spring set the standard for all other aftermarket helper springs. Featuring Progressive Spring Rate and Fulltime Spring Rate design, this spring is the workhorse of the Hellwig Spring line. With the Progressive design the vehicle must be loaded and its spring compressed to activate the Hellwig spring, therefore as the vehicles load increases the Hellwig helper spring progressively increases its resistance to the load. In the Fulltime design the Hellwig spring immediately reacts to the vehicles load, therefore compressing very little as load is applied to the vehicle.

Manufactured with heat treated ASTM 5160 alloy spring steel these units increase your vehicles level load carrying capacity up to the manufacturer's Gross Vehicle Weight Rating¹. Designed to install on full size pick-up trucks and vans, this unit requires mounting hardware to install properly on a 2 1/2 " wide spring or 3" wide leaf springs. When ordering be sure to identify the spring kit and the appropriate mounting hardware kit to complete the installation. Simple bolt on design using common hand tools provide the installer ease of installation and the vehicle owner hassle free use. "Set it and forget it". The LP 25 is rated at 2500lbs level load carrying capacity and the LP 35 is rated at 3500lbs level load carrying capacity, not exceed the vehicles GVWR¹.

Trac-Bars

The perfect compliment to a Hellwig Motorhome Sway Bar, this unit controls lateral movement of the vehicles leaf springs. By aligning and maintaining the axle laterally under the frame your motorhome will track better with less wandering and rut chasing. These units provide reduced driver fatigue, less driver corrections, increased vehicle control and improved driving confidence. Bolt-on design allow for installation with common hand tools. Kits include all the components necessary to complete you installation including powder coated brackets, zinc plated hardware and installation instructions.

- Gross Vehicle Weight Rating, GVWR. The rating assigned to a vehicle stating the maximum allowable load for that vehicle. For example a vehicle with a 6500lb GVWR limits the maximum load of the vehicle and its payload to 6500lbs.
- ² Hellwig works hard to design kits that bolt directly to your vehicle. In some instances and for maximum effectiveness of your installation drilling may be required.