



INSTALLATION INSTRUCTIONS

INSTALLATION INSTRUCTIONS

- 1 • Clean the vehicle before installation of the Hood Protector.
 Trial fit Hood Protector centrally onto hood. Remove rubber seal retaining plugs that line up with Hood Protector slots, discard retaining plugs. With a non-permanent marker, mark the positions of the four acrylic tag slots in the Hood Protector onto hood. Also note and mark the metal wing clip positions corresponding to the outer holes of Hood Protector. Remove Hood Protector.
- 2 • Clean the noted areas under the wing clip locations with alcohol wipe provided. Wipe off any residue with a dry clean cloth. Adhere the abrasive resistant tape strips over the hood lip. Apply tape so approximately half of each strip is adhered to the top side and half is adhered to the underside of hood.
- 3 • Slide the metal wing clips over the abrasive resistant tape strips on the hood lip.
IMPORTANT: Ensure that the clips are positioned over abrasive resistant tape and do not come in contact with any of the hood's paint work. Failure to do this may result in permanent paint damage.
- 4 • Insert the screw plugs provided into the four vacant holes.
- 5 • Re-install the Hood Protector, ensure that the collar of the screw plugs locate into and parallel with the slots in the Hood Protector tags, as shown.
- 6 • Place rubber seal over acrylic tags. While maintaining thumb pressure against the underside of the Hood Protector, insert large washer and self-tapping screw through the rubber seal and into the screw plug and tighten screws. Do not fully tighten yet. Ensure the Hood Protector is centralised on hood then fully tighten screws.
Important: Thumb pressure must be maintained on the Hood Protector to prevent the screw plug from rotating. DO NOT OVERTIGHTEN SCREWS.
- 7 • Fasten Hood Protector with screws and small washers provided to the outer holes.
TO REMOVE: Reverse the above procedure.

To Clean: Use mild detergent and water solution (Do NOT use solvents). Avoid the use of automatic "Brush Style" car washes. When closing the hood, do NOT pull on Hood Protector.



- Do not use power tools to install this product.
- No battery operated screw guns.
- The use of power tools during installation may void the product warranty.
- Do not overtighten.

