

44487
08-10 JEEP
LIBERTY



44487
08-10 JEEP
LIBERTY

08-10 JEEP LIBERTY **Sport Series Grille**

TOOLS REQUIRED:
Flat Head Screwdriver

PARTS LIST
(7) Sport Series Grilles

Step 1 Grille Removal

PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION. Remove the 8 clips on the radiator cover with a flat head screwdriver by prying the top of them up until they pop, then pry up the base of the clip until it pops out of the cover. (Fig 1) On the upper sides of the grille shell are 2 tabs that need to be that need to be unlatched.

Step 2

Unhook the hood release cable from the clips holding it to the radiator cover. (Fig 2)

Step 3

Unhook 2 tabs on the lower part of the grille shell, they are located at the lower outer corners below the headlamps. Use a small flathead screwdriver to reach between the grille shell and the headlight and press the tab down, pull the grille shell outward until it clears the tab. (Fig 3) Remove the grille shell from the vehicle.

Step 4

Next remove the black plastic grille back from the painted grille shell. Do this by prying the small tabs that hold the 2 pieces together, there are about a dozen of these tabs. (Fig 4)

Step 5 Install the 7 Grilles into the Grille Shell

Next install the 7 Sport Series grilles into the grille shell. Do this by pushing the grilles into the openings on the grille shell until they are seated flush. This may require a little force, be careful as the grilles can have sharp edges. (Fig 5)

Step 6

Next is to replace the black plastic grille backing onto the shell, make sure all of the small tabs snap back into place. (Fig 6)

Step 6 Reinstalling the completed Grille onto the vehicle

Next is to reinstall the completed grille shell back onto the vehicle. Attach the 2 lower tabs first and then the 2 upper tabs. Reinstall the 8 clips and secure the hood latch cable back under the tabs.

