

55516
05-09
MUSTANG GT



55516
05-09
MUSTANG GT

TOOLS REQUIRED:

Phillips / Slotted Screwdrivers
Drill & 1/4" Drill Bit
3/8", 10mm Sockets
Drill & 3/16 Drill Bit

PARTS LIST:

1- mesh grille
6- 10-32 nylon lock nuts
6- #10 Flat washer
2- 2" Flange Bracket

Read and understand instructions before attempting installation

Step 1

Remove the top radiator cover and the 10mm bolts on each end of the grille. The plastic retainers are removed by pulling the center pin out. Now remove the four bolts along the bottom; these hold the engine splash shield to the bumper cover. The wheel well splash-shields are held to the bumper cover with Phillips head retainers (three each side).



Step 2

Use a 10mm socket to remove the three nuts retaining each end of the bumper cover. Disconnect the driving lights in the grille from the harness; disconnect the signal lights in the bumper. Release the bumper cover on each end of the grille. Pull the bumper cover up over the detent in the molded into the core support (1). Remove the bumper cover.

Step 3

Center the grille over the factory bumper grille; mark where the studs align to the plastic insert. Drill a 3/16" hole at each mark (2 & 3). Install the grille; make sure the grille is centered correctly. Install flange brackets to retain the center (4); thread a washer and nylon lock nut on each stud. Tighten hardware until grille is held firmly in place. Do not overtighten. Re-install the bumper cover assembly and radiator cover back onto the vehicle.

