



PERFORMANCE EXHAUST SYSTEMS

**INSTALLATION INSTRUCTIONS
DUAL REAR EXHAUST
2006 CADILLAC STS-V 4.4L SUPERCHARGED RWD
PART # 316000**



ITEM	PART #	QUANTITY	DESCRIPTION
A	700860	1	Passenger side muffer assembly w/welded 4" tip
B	700861	1	Driver side muffer assembly w/welded 4" tip
C	5757	2	2 1/2" Clamp

Thank you for purchasing our Gibson exhaust system for your vehicle. If you need further assistance, please do not hesitate to call our technical dept at (800) 528-3044 Monday through Friday, 8:00 am to 5:00 pm. 0806

CAREFULLY READ INSTRUCTIONS BEFORE STARTING INSTALLATION.

When installing this exhaust system make sure to use proper safety precautions. Use jack stands when working under the vehicle, set parking brake, block tires and use safety glasses and gloves. Allow exhaust to cool before attempting installation. Severe injury or burns could occur if safety measures are not taken.

SUGGESTED TOOLS: 1/2", 9/16" 15mm wrenches & sockets, WD-40, hacksaw, jack stands.

.....
• **Disconnect the negative battery cable before removal of OEM exhaust. This will allow the computer to reset and recognize the new exhaust. Lay out the exhaust on the floor so it looks like the drawing and compare parts with manual.**
.....



1. To remove the stock exhaust, cut off stock muffler just after the 90 degree bend just behind the rear axle as shown in the pictures. Disengage welded hangers from rubber grommets to remove stock muffler. **DO NOT** damage rubber grommets they will be reused to install the new exhaust.



2. To install driver side muffler assembly #A, insert welded hangers into rubber grommets. Use clamp #C to secure to stock tailpipe. Adjust muffler assembly to best suit your vehicle and tighten clamp.



3. To install passenger side muffler assembly #B, insert welded hangers into rubber grommets. Use clamp #C to secure to stock tailpipe. Adjust muffler assembly to best suit your vehicle and tighten clamp.



4. Use stainless steel cleaner and a Scotch Brite pad weekly to prevent tip from discoloration.