



P/N 2287HKR (Painted) & 2287-1HKR (Coated)

Super Competition Headers
1970-72 Camaro

Super Competition Engine Swap Headers
1973-81 Camaro & 1970-81 Firebird, Trans Am – Chevy V8
(396-502)

NOTE: Factory style big block frame stands and motor mounts **MUST** be used to ensure proper engine locations and header fit. 67-69 Camaro & 73-75 Nova versions are currently available from "Rick's Camaro" at 1-800-359-7717 or www.rickscamaro.com.

NOTE: Use ARP 12-point head bolts.

Thank you for making HOOKER HEADERS your choice in a high-performance exhaust system. Extensive dyno/track testing has enabled HOOKER to offer the most advanced design in exhaust systems. The installation, while not complex, will take a certain amount of time. However, the additional horsepower and improved performance will more than justify your efforts. Proper installation and maintenance will ensure long life and maximum performance from your hooker exhaust system.

WARNING! Breaking in an engine with ceramic-coated headers WILL result in damage to the coating and will VOID all warranties. Ceramic-coated headers require several heat cycles to fully cure before they will withstand extreme heat. HOOKER recommends using a cast-iron exhaust manifold or an old header to break in new engines to avoid coating damage.

BEFORE STARTING

Your vehicle must be raised a minimum of 36 inches. A floor hoist is ideal. If no hoist is available, we strongly urge the use of axle stands as a safety measure.

CAUTION! YOUR CAR SHOULD NOT BE SUPPORTED ON A BUMPER JACK.

INSTALLATION PROCEDURE – PLEASE READ CAREFULLY

LEFT SIDE

1. Disconnect the battery cable to avoid damage to the car's electrical system.
2. Remove the stock exhaust manifold and spark plugs.
3. Remove the clutch linkage.
4. Remove the oil filter and pressure sending unit.
5. Remove the bell crank and lower rod from the transmission locking device.
6. Starting from the bottom, work the header through the chassis and position in line with ports (be careful not to damage the head sending unit).
7. Place gaskets into position.
8. Start all bolts (most restricted first).
9. Tighten all bolts evenly.
10. Replace clutch linkage, oil filter, pressure sending unit, and plugs.

RIGHT SIDE

1. Remove the stock exhaust manifold and spark plugs.
2. Remove the starter.
3. Remove the bolt from the motor mount.
4. Jack up the motor (use a board between the pan and jack).
5. Starting from the bottom, work the header up through the chassis. Before you place into position, install the starter.
6. Lower the engine and replace the mount bolt.
7. Place gasket into position.
8. Start all bolts (most restricted first).
9. Tighten all bolts evenly. Replace the spark plugs.
10. To connect the headpipes to the collector, purchase Hooker Header Reducer Kit No. 11035HKR.
11. Connect the battery, start the engine, and check for leaks. Be sure all brake lines, fuel lines, and electrical wires have sufficient clearance. Reroute, as necessary.

When finished, give your car a test drive checking carefully for any new noises. After several days driving, retighten all bolts.

Any questions? Please contact Technical Service: 1-866-GOHOLLEY or 270-781-9741. For online help, please refer to the website: www.holley.com.

LIMITATION OF LIABILITY – DISCLAIMER:

The regulation of emissions production, noise levels, and safety standards is undertaken by the federal government, each of the fifty state legislatures, and by many local municipalities, towns, and counties.

HOKKER makes no warranties of merchantability, of fitness for particular purpose, or that its products are approved for general use, or that its products are approved for general use, or that its products comply with laws, regulations, or ordinances in the state where they may be sold to the ultimate purchaser, the consumer.

Unless expressly stated to the contrary in the catalog, instruction sheet; or price list, the entire risk as to the conformity of any company product in any such state and as to repair should the product prove to be defective or non-conforming, is on the retail purchaser, the buyer, the ultimate consumer, of such product and it is not upon the seller, distributor, or manufacturer.

In this connection, the retail purchaser, the buyer, the ultimate consumer assumes the burden of the entire cost of any and all necessary service, alterations, or repair.

THE FOREGOING STATEMENT LIMITS THE LIABILITY OF THE MANUFACTURER.

California vehicle code, sections 27156 AND 38391, prohibits the advertising, offering for sale, or installation of any device, which modifies a vehicle's emission control system, unless exempted, unless otherwise noted. HOKKER Headers have not received an exemption from these code sections and are to legal for sale or use in California on vehicles originally equipped with catalytic converters, it is illegal, except for racing vehicles, which may never be driven upon a highway. To remove or otherwise render inoperative any emission control device on the regulated motor vehicles – check catalog listings to ensure proper application in the other 49 states, unless otherwise noted, HOKKER Headers are not legal for pollution-controlled motor vehicles, except for racing vehicles, which may never be used upon a highway and are not intended or applicable for highway use.

2287HKR

Revision Date: 8-18-10