

## **Installation Instructions for 79023**

### **Scissor jack**

**1 1/2 ton Capacity**

#### **Warning**

1. Study, understand and follow all instructions before operating this device.
2. Do not exceed rated capacity as designated by the height/capacity curve.
3. Use only on hard level surface.
4. Use for emergency tire changing only.
5. Never get beneath the vehicle when it is supported by the jack.
6. Activate the hazard warning flasher, turn off ignition, set parking brake, move automatic shift selector to park position. In case of a manual transmission, move gear selector into reverse position. In addition, the wheel diagonally opposite from the wheel being lifted shall be chocked in both directions.
7. Lift only on areas of the vehicle as specified by the vehicle manufacturer.
8. Follow tire changing procedure as per the vehicle manufacturer's owner's manual.
9. No alterations shall be made to this product.
10. Failure to heed these messages may result in personal injury and/or property damage.

#### **Before Use**

1. Check before each use for abnormal conditions such as cracked welds, leaks, damaged, loose or missing parts.
2. Inspect the jack immediately if lift is believed to have been subjected to an abnormal load or shock.
3. If the jack is found to be damaged, it should be removed from service until properly repaired.

#### **Operating Instructions**

1. Insert the jack handle into the hole of the handle socket.
2. Make sure that the saddle is correctly positioned. To prevent damage to the jack, do not move the jack while the handle is intact in the socket.
3. To raise load, use one hand to hold the front part of the handle and use the other hand to turn at the rear and of the handle clockwise.
4. To lower load, use one hand to hold the front part of the handle and use the other hand to turn at the rear and of the handle counterclockwise slowly.

#### **Care & Maintenance**

1. When jack is not in use, lifting arm should be in full down position.
2. Always keep jack clean and keep the screw and bearings well lubricated.
3. Store the handle with care.



**1-800-345-4545 [jeps.com](http://jeps.com)**