



Genuine Parts

PRECAUTIONS:

- ❑ Read ALL instructions before installing instrument.
- ❑ Follow ALL safety precautions when working on vehicle-wear safety glasses!
- ❑ ALWAYS disconnect (-) negative battery cable before making electrical connections.

HELP?:

- ❑ If after reading these instructions you don't fully understand how to install your instrument(s), contact your local Stewart Warner distributor, or contact our Technical Support Team toll free at **1-800-676-1837**
- ❑ Additional applications information may be found at www.stewartwarner.com.

Installation Instructions
Mechanical Gauge Tubing Kit

1

2

TUBING KIT INSTALLATION (Figure 1):

1. Assemble nylon tube and fittings as shown.
2. Route nylon tube to gauge clear of moving or hot engine components. Protect nylon tube from sharp edges through firewall using a rubber grommet.

NOTE: When being used with vacuum gauge you may choose to connect to a vehicle vacuum line. In this case, a proper "T" fitting should be selected with two barb fittings properly sized for the vacuum line used and a 1/8 NPTF for the tube kit to connect to

CAUTION: Nylon tubing is not recommended for use with fuel pressure gauges. Use metal or braided fuel lines.

WARRANTY INFORMATION:

TWO (2) YEAR LIMITED WARRANTY. Stewart Warner products are warranted against defects in workmanship and materials for a period of two (2) years from the date of purchase. Proof-of-purchase is required; otherwise, the warranty period shall default to two (2) years from date-of-manufacture (as indicated by the date code on the product). See detailed Warranty Policy for other Terms & Conditions.

STEWART WARNER
1-800-676-1837

www.stewartwarner.com

