

AccuCharge® Instructions

Read the following steps completely before beginning. If you have any questions after reading these instructions, please contact Spectre Performance Tech Support by email at Tech@SpectrePerformance.com or call our Tech Department @ 1-909-673-9800 Monday through Thursday, 6:00am to 4:30pm PT.

Step 1: Remove the filter from your vehicle.

Step 2: Gently tap the filter against the inside of your trash can to remove the external dirt particles (it can make a mess, so we found it most convenient to tap it against something you won't have to clean up later!). Tap it so the dirty side is towards the surface you are tapping.

Step 3: Spray the filter with the Spectre Air Filter Cleaner and allow the solution to soak in for about 10 minutes.

Step 4: Rinse the filter with warm water, clean side to dirt side, to flush out the dirt. **Do not use high pressure sprayers or hose nozzles as they can damage the filter.**

Step 5: Allow the filter to dry. Placing it in a warm area or in sunlight will help to speed up the drying process. Do not use any direct heat source (heat gun, hair dryer, etc.) as it may damage the filter.

Step 6: Identify the filter you are servicing. All OEM replacement filters, and most cone filters, have part numbers molded into them. There are, however, a few filters that do not - Our cone-style filters with chrome lids can be identified by measuring the overall length – 3.7" = 8162 (P2), 6.7" = 8132 (P4), and 10.5" = 9732 (P5). Our P3 filters, with black lids, can be identified by measuring the overall length – 6.25" tall with 3" inlets = 9132. You can also find part numbers on our online catalog at SpeedbySpectre.com. If you need further assistance in determining which filter you have, please email Tech@SpectrePerformance.com or call our Tech Department @ 1-909-673-9800 Monday through Thursday, 6:00am to 4:30pm PST.

Step 7: Determine the required oil amount from the chart on the next page of these instructions.

Step 8: Although the Spectre filter oil does not require any dyes for function, we have included a red dye packet which can be added to make the oil red. If you have a red filter, add the red dye packet to the oil and shake until fully mixed. If you have a blue or white filter, do not add this dye.

Step 9: Apply the required amount of oil to the filter by spraying it on the media evenly. There will be a small amount of overspray so be sure to take appropriate action to protect the surrounding area. **DO NOT APPLY MORE OIL THAN RECOMMENDED IN THE CHART! We have carefully calculated the oil requirements of each of our filters. Over-oiling can cause a decrease in air flow and performance.**

Step 10: Wipe any overspray off of the filter lid, base, and name plate and re-install the filter.

PART NO.	REQUIRED OIL (mL)		PART NO.	REQUIRED OIL (mL)		PART NO.	REQUIRED OIL (mL)
8132	21		886479	33		888918	32
8136	21		886555	40		888925	78
8138	21		886690	22		888997	26
8162	10		886807	14		889332	18
8166	10		886850	26		889345	20
8168	10		887344	17		889360	27
9132	9		887351	24		889401	69
9136	9		887417	32		889482	16
9138	9		887420	9		889564	18
9732	34		887421	24		889589	130
9736	34		887432	18		889605	23
9738	34		887440	32		889606	12
880100	10		887597	21		889607	10
880136	24		887598	14		889608	10
880138	35		887626	45		889609	12
880139	44		887640	100		889610	14
880160	29		887730	16		889611	19
880192	33		887774	13		889612	23
880326	34		888038	40		889613	10
880351	21		888039	35		889614	19
882606	12		888040	13		889687	20
883300	18		888080	20		889778	20
883559	13		888133	20		889831	16
883588	24		888205	32		889832	8
883647	12		888208	30		889838	19
883901	30		888221	30		889881	21
883914	32		888241	31		889882	19
883915	14		888243	35		889883	19
883916	17		888602	28		889884	19
884309	36		888606	17		889886	12
884808	13		888699	12		889888	11
884810	12		888755	65		889895	30
884813	12		888756	35		889969	14
884939	17		888805	16		8810014	21
885056	21		888817	37		8810165	22
886366	28		888911	10			