

INSTALLATION INSTRUCTIONS
BULL BAR
05-07 DODGE DAKOTA
PART # 72040

PARTS LIST:

1	Bull Bar	4	10-1.50mm x 30mm Hex Head Bolts
1	Driver/Left Mounting Bracket	4	10mm Lock Washer
1	Passenger/Right Mounting Bracket	4	10mm Hex Nuts
		8	10mm ID x 26mm OD x 3mm Flat Washers

PROCEDURE:

- 1. REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION.**
- 2. NOTE:** It may be necessary to remove/relocate front license plate and license plate bracket. It is not required, but strongly recommended. If local/state law requires a license plate, license plate relocation kit is available.
3. From underside of vehicle, remove factory tow hooks. **NOTE:** Tow hooks may not be mounted in conjunction with the Bull Bar.
4. Determine passenger and driver Mounting Brackets and partially hang them from vehicle with factory tow hooks bolts.
5. With help position Bull Bar on the outer side of Mounting Brackets. Attach Bull Bar to Mounting Brackets using the included (4) 10mm x 30mm Hex Head Bolts, (4) 10mm Lock Washers, (4) 10mm Hex Nuts, and (8) 10mm Flat Washers.
6. Adjust Bull Bar properly, and then tighten all hardware at this time.
7. Do periodic inspections to the installation to make sure that all hardware is secure and tight.
8. To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish.
For stainless steel: Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap may be used also to clean the Sidebar.
For gloss black finishes: Mild soap may be used to clean the Sidebar

STEELCRAFT

(Passenger Side Mounting Bracket Shown)

