



**P/N 89590 TIRE PRESSURE GAUGE COVER
INSTALLATION INSTRUCTIONS**

1. Remove the hose from the gauge by unthreading the chrome pressure release fitting from the bottom of the gauge.
2. Very lightly coat the inside of the rubber gauge cover with a silicone lubricant to facilitate assembly.
3. Insert the gauges hose fitting through the square hole in the side of the gauge cover first, then push the cover up and over the rest of the gauge.

For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437-2116

Visit Us At www.moroso.com

89590INST

Rev. B
060311



**P/N 89590 TIRE PRESSURE GAUGE COVER
INSTALLATION INSTRUCTIONS**

1. Remove the hose from the gauge by unthreading the chrome pressure release fitting from the bottom of the gauge.
2. Very lightly coat the inside of the rubber gauge cover with a silicone lubricant to facilitate assembly.
3. Insert the gauges hose fitting through the square hole in the side of the gauge cover first, then push the cover up and over the rest of the gauge.

For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437-2116

Visit Us At www.moroso.com

89590INST

Rev. B
060311



**P/N 89590 TIRE PRESSURE GAUGE COVER
INSTALLATION INSTRUCTIONS**

1. Remove the hose from the gauge by unthreading the chrome pressure release fitting from the bottom of the gauge
2. Very lightly coat the inside of the rubber gauge cover with a silicone lubricant to facilitate assembly.
3. Insert the gauges hose fitting through the square hole in the side of the gauge cover first, then push the cover up and over the rest of the gauge.

For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437-2116

Visit Us At www.moroso.com

89590INST

Rev. B
060311



**P/N 89590 TIRE PRESSURE GAUGE COVER
INSTALLATION INSTRUCTIONS**

1. Remove the hose from the gauge by unthreading the chrome pressure release fitting from the bottom of the gauge.
2. Very lightly coat the inside of the rubber gauge cover with a silicone lubricant to facilitate assembly.
3. Insert the gauges hose fitting through the square hole in the side of the gauge cover first, then push the cover up and over the rest of the gauge.

For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437-2116

Visit Us At www.moroso.com

89590INST

Rev. B
060311



**P/N 89590 TIRE PRESSURE GAUGE COVER
INSTALLATION INSTRUCTIONS**

1. Remove the hose from the gauge by unthreading the chrome pressure release fitting from the bottom of the gauge
2. Very lightly coat the inside of the rubber gauge cover with a silicone lubricant to facilitate assembly.
3. Insert the gauges hose fitting through the square hole in the side of the gauge cover first, then push the cover up and over the rest of the gauge.

For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437-2116

Visit Us At www.moroso.com

89590INST

Rev. B
060311



**P/N 89590 TIRE PRESSURE GAUGE COVER
INSTALLATION INSTRUCTIONS**

1. Remove the hose from the gauge by unthreading the chrome pressure release fitting from the bottom of the gauge.
2. Very lightly coat the inside of the rubber gauge cover with a silicone lubricant to facilitate assembly.
3. Insert the gauges hose fitting through the square hole in the side of the gauge cover first, then push the cover up and over the rest of the gauge.

For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437-2116

Visit Us At www.moroso.com

89590INST

Rev. B
060311