



BTR-TWINTURBOSTG3

GEN III & IV LS APPLICATIONS


INTAKE DURATION @.050"	226 °	ROCKER ARM RATIO	1.7 :1
EXHAUST DURATION @.050"	24X °	NET LIFT INTAKE	0.618 "
LOBE LIFT INTAKE	0.364 "	NET LIFT EXHAUST	0.618 "
LOBE LIFT EXHAUST	0.364 "	LOBE SEPARATION ANGLE	115 °
INTAKE LOBE LIFT @ T.D.C.	0.0495 "	ACTUAL SPECS MAY VARY*	

REV.2

INSTALL DOT-DOT (SEE DIAGRAM ON REVERSE SIDE)

LS TWIN TURBO STAGE 3 V2

TIMING CHAIN ORIENTATION




INSTALL DOT-DOT

TORQUE SPECIFICATIONS

CAMSHAFT SPROCKET (3-BOLT)	26 FT/LBS
CAM RETAINER PLATE BOLT (HEX)	18 FT/LBS
CAM RETAINER PLATE BOLT (TORX)	11 FT/LBS

IMPORTANT NOTE:

BE SURE TO THOROUGHLY CLEAN CAMSHAFT,
INCLUDING THE CENTER, AND APPLY
ASSEMBLY LUBE BEFORE INSTALLATION



FOR MORE SPECS AND TECHNICAL INFO SCAN
THE QR CODE OR VISIT:

BRIANTOOLEYRACING.COM/TECHNICAL