



BTR-LS TRUCK STG1-V3

GEN III & IV LS APPLICATIONS


INTAKE DURATION @.050"	201 °	ROCKER ARM RATIO	1.7 :1
EXHAUST DURATION @.050"	21X °	NET LIFT INTAKE	0.542 "
LOBE LIFT INTAKE	0.319 "	NET LIFT EXHAUST	0.542 "
LOBE LIFT EXHAUST	0.319 "	LOBE SEPARATION ANGLE	111 °
INTAKE LOBE LIFT @ T.D.C.	0.0284 "	ACTUAL SPECS MAY VARY*	

REV.0

INSTALL DOT-DOT (SEE DIAGRAM ON REVERSE SIDE)

BTR LS TRUCK V3 STAGE 1

TIMING CHAIN ORIENTATION



INSTALL DOT-DOT

TORQUE SPECIFICATIONS

CAMSHAFT SPROCKET (3-BOLT)	26 FT/LBS
CAM RETAINER PLATE BOLT (HEX)	18 FT/LBS
CAM RETAINER PLATE BOLT (TORX)	11 FT/LBS

IMPORTANT NOTE:

BE SURE TO THOROUGHLY CLEAN CAMSHAFT, INCLUDING THE CENTER, AND APPLY ASSEMBLY LUBE BEFORE INSTALLATION



FOR MORE SPECS AND TECHNICAL INFO SCAN THE QR CODE OR VISIT:

BRIANTOOLEYRACING.COM/TECHNICAL