

Kit Part #	51/54/75-10932-1 75-10932-1V
-------------------	---------------------------------

Model:	Year:	Engine:
Ram 2500	'03-'07	L6-5.9L (td)
Ram 3500	'03-'07	L6-5.9L (td)
Ram 2500	'07.5-'10	L6-6.7L (td)
Ram 3500	'07.5-'10	L6-6.7L (td)














5/16" Nut Driver
13mm Socket
9/16" Socket or Wrench
Ratchet and Extension
Small Flat Screwdriver
5/32" Hex Key (Allen Wrench)

1	Air filter replacement P/N: (24-91026 <i>Pro 5R™</i> or 72-90021 <i>Pro-GUARD 7™</i> or 21-90021 <i>ProDry 5™</i>)
1	Cover, filter housing
1	High Temp Coupler 4" x 2.5"
2	Clamps #064
2	3/8" hex head bolts
4	3/8" flat washer
2	Nuts, 3/8", self-locking
1	Screw, 1/4"-20 hex flange
1	Filter housing
4	Screw, Socket Hex Head
4	Washer, Wavy: M6

- | | | | |
|---|-------------------------------------|---|---------------------|
| 1 | Plug, 05-01068 | 1 | Torx Bit T20 |
| 1 | Nut, 1/4" Self-locking | 1 | Grommet Rubber |
| 1 | Washer, Flat | 1 | Gasket, Temp Sensor |
| 1 | Sensor Gasket | 1 | Plate, Mas Sensor |
| 3 | Screw, Slotted 8-32 x 5/8" | 1 | Tube |
| 1 | "L" Bracket (Use only on 2003-2009) | | |
| 1 | Bracket 05-01114 (Use only on 2010) | | |
| 2 | Screw, Phillips MS | | |

Note: Filter removal for cleaning will require screw removal (Step 12) and lift tube for clearance. It is not necessary to loosen turbo clamps.

1 Air filter P/N (**Pro Dry S™** 21-90021)
1 Restore Kit, Gold Squeeze
1 Pre-filter

06-80142 Rev B
Last Updated 2-2010