

11568

88-89 MERCURY TRACER

12/14/2012

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 1,000 LBS. TRAILER WEIGHT & 100 LBS. TONGUE WEIGHT.


DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.

WARNING: ALL NON-TRAILER LOADS APPLIED TO THIS PRODUCT MUST BE SUPPORTED BY 18050 STABILIZING STRAPS.

** FAILURE TO PROPERLY SUPPORT NON-TRAILER LOADS WILL VOID PRODUCT WARRANTY**

HAVING INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-800-798-0813

Parts List			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	2	5/8-11 x 1 1/2 HEX BOLT	5/8-11 HEX BOLT
2	2	5_8 LOCK WASHER	HELICAL LOCK WASHER
3	2	5/8	WASHER
4	2	5_8 - 11 HEX-NUT	HEX NUT
5	4	3/8 - 16 x 1 1/4	HEX BOLT
6	2	3/8"	FENDER WASHER
7	4	3/8"	LOCK WASHER
8	4	3/8 - 16	HEX NUT
9	1	CM-11568-MBWA	MAIN BODY WELDMENT ASSEMBLY
10	1	CM-11568-BMWA	BALL MOUNT WELDMENT ASSEMBLY



HITCH WEIGHT: 22 LBS.

INSTALL TIME

PROFESSIONAL: 30 MINUTES

NOVICE (DIY): 60 MINUTES

INSTALL NOTES:

- ASSEMBLE HITCH
- REMOVE SPARE TIRE
- DRILLING REQUIRED
- SILICONE SEAL HARDWARE

INSTALLATION STEPS

1. Attach CM-11568-MBWA to CM-11568-BMWA as shown. Temporarily remove the spare tire.
2. Lift the assembled hitch into position under the vehicle so the hitch fits between the vehicle's slotted brackets projecting from the bottom of the tire well. Fasten the hitch to the brackets using fasteners as shown. Place flat washers against the outside of the slotted brackets.
3. Using the hitch as a template drill the spare tire well for 3/8" diameter hardware. Install fasteners at these holes noting that the fender washers are installed inside the tire well, opposite the hitch.
4. Torque all 3/8" fasteners to 45 lb-ft, and all 5/8" fasteners to 210 lb-ft.
5. Use silicone sealant to seal hardware installed through spare tire well.
6. Reinstall spare tire removed in Step 1.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

Curt Manufacturing Inc., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.