

# 18121 FOLDING SHANK CARGO CARRIER

MAXIMUM GROSS LOAD CAPACITY: 500 LBS.

**\*\*\*DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED LOAD CAPACITY.\*\*\***

**\*\*USE OF TOWING CARRIERS REDUCES HITCH TOW RATINGS\*\***

| Parts List |     |                      |                       |
|------------|-----|----------------------|-----------------------|
| ITEM       | QTY | PART NUMBER          | DESCRIPTION           |
| 1          | 12  | 1_4 - 20 x 3_4 HEX   | HEX BOLT              |
| 2          | 12  | 1_4 LOCK WASHER      | 1/4" LOCK WASHER      |
| 3          | 24  | 1/4"                 | WASHER                |
| 4          | 12  | 1_4 - 20 HEX NUT     | HEX NUT               |
| 5          | 4   | 3_8 - 16 x 1         | HEX BOLT              |
| 6          | 3   | 3_8 - 16 x 3 1_2 HEX | HEX BOLT              |
| 7          | 14  | 3/8"                 | WASHER                |
| 8          | 7   | 3/8"                 | LOCK WASHER           |
| 9          | 7   | 3/8 - 16             | HEX NUT               |
| 10         | 1   | 1_2 - 13             | NYLOCK HEX NUT        |
| 11         | 1   | 1/2-13 x 3           | HEX BOLT              |
| 12         | 1   | CM-18121-014         | .375" SOLID ROUND PIN |
| 13         | 1   | CM-18121-013         | 1/2" HITCH PIN CLIP   |

## NOTE:

LOOSELY INSTALL ALL FASTENERS THEN TORQUE ALL 3/8" FASTENERS TO 30 LB-FT AND ALL 1/4" FASTENERS TO 8 LB-FT. TIGHTEN 1/2" FASTENERS ENOUGH TO ALLOW ROTATION IN COUPLER.

