

Spohn Performance, Inc.

494 E Lincoln Ave Myerstown, PA 17067

1-888-365-6064 www.spohn.net

Part # 14019274 – Strut to Upper Strut Mount Mounting Nuts 1982-1992 GM F-Body

USE OF THIS PRODUCT IS ACCEPTANCE OF SELLER'S DISCLAIMER OF WARRANTY!

By their very nature, competition components are constantly pushed to their limits. While our components are designed to withstand intense race conditions, it is impossible to control the quality of installation or the varying conditions in which they are used. It is for this reason that absolutely no warranty or guarantee is either written or implied. Neither the seller nor the manufacturer will be liable for any loss, damage, or injury – direct or indirect – arising from the use of or inability to determine the use of any product. Before using, the user should determine the suitability of the product for its intended use, and the user shall assume all responsibility in connection therewith. Spohn Performance, Inc. makes no guarantee as to the legality for any specific class. Spohn Performance, Inc. makes no claims, nor does it intend its products to be used in street driven vehicles. Spohn Performance, Inc. reserves the right to make changes in design or add to or improve on their product without incurring any obligation to install the same on product previously manufactured. The Buyer agrees to indemnify and hold Spohn Performance, Inc. harmless from any claim, action or demand arising out of or incident to the Buyer's installation or use of products purchased from Spohn Performance, Inc.

INSTRUCTIONS

These nuts are no longer available from GM. They secure the top of the front struts to the upper strut mounts on the 1982-1992 GM F-Body Camaro and Firebird.

The bottom of the nut has a special conical shape that seats into the bearing on the upper strut mount, so a regular nut, or a regular flange nut will not work.

These were discontinued long ago by GM. These nuts are an exact replica of the OEM GM hardware. They are forged from 4130 chrome moly and then CNC machined. Finally, they are silver zinc plated for corrosion protection.

Wrench Size: 22mm

Torque Value: 136 ft./lbs.