

# Spohn Performance, Inc.

494 E Lincoln Ave Myerstown, PA 17067

1-888-365-6064    www.spohn.net

## Part #984 – 4140 Chrome Moly Tie Rod Adjusters

### USE OF THIS PRODUCT IS ACCEPTANCE OF SELLER'S DISCLAIMER OF WARRANTY!

By their very nature, competition components are constantly pushed to their limits. While our components are designed to withstand intense race conditions, it is impossible to control the quality of installation or the varying conditions in which they are used. It is for this reason that absolutely no warranty or guarantee is either written or implied. Neither the seller or the manufacturer will be liable for any loss, damage, or injury – direct or indirect – arising from the use of or inability to determine the use of any product. Before using, the user should determine the suitability of the product for its intended use, and the user shall assume all responsibility in connection therewith. Spohn Performance, Inc. makes no guarantee as to the legality for any specific class. Spohn Performance, Inc. makes no claims, nor does it intend its products to be used in street driven vehicles. Spohn Performance, Inc. reserves the right to make changes in design or add to or improve on their product without incurring any obligation to install the same on product previously manufactured. The Buyer agrees to indemnify and hold Spohn Performance, Inc. harmless from any claim, action or demand arising out of or incident to the Buyer's installation or use of products purchased from Spohn Performance, Inc.

**Hex Coupler:** 15/16" o.d. x 4.00" long x 5/8"-18 threads (RH/LH)

Use Anti-Seize compound on the threads of the tie rod ends before installing.

Hex Adjuster Wrench Size: 15/16"

Jam Nut Wrench Size: 15/16"

**Thread Note:** Many times the tie rod ends themselves have poor thread quality that will not match our CNC machined thread quality on the adjusters. You may need to run a 5/8"-18 (fine) thread die over the tie rod end threads to obtain quality threads on the tie rod ends. Be sure to use the proper left or right hand threaded die on the tie rod ends.