

EGR

INSTALLATION INSTRUCTIONS

INSTALLATION INSTRUCTIONS

1. Clean the vehicle before installation of the Hood Protector. Trial fit Hood Protector centrally onto hood. With a non-permanent marker, mark the positions of the two center push on clips. Also note and mark the bumpstops in the hood that correspond with the holes in the Hood Protector. Remove Hood Protector and Bumpstops.
2. Clean the noted areas under the center push on clip locations with the alcohol wipe provided. Wipe off any residue with a dry clean cloth. Adhere the abrasive resistant tape strips over the hood lip. Apply tape so approximately half of each strip is adhered to the top side and half is adhered to the underside of hood.
3. Push the metal wing clips onto hood locating the metal wing clips over the abrasive resistant tape strips on the hood lip, as shown
IMPORTANT: Ensure that the clips are positioned over abrasive resistant tape and do not come in contact with any of the hood's paint work. Failure to do this may result in permanent paint damage.
4. At the previously noted wing positions, insert the screw plugs into the vacant holes on the hood.
5. Re-install the Hood Protector. While maintaining thumb pressure against the underside of the Hood Protector, insert self-tapping screw through large washer and into the screw plug then tighten screws. Do not fully tighten yet. Ensure the Hood Protector is centralised on hood then fully tighten screws.
Important: Thumb pressure must be maintained on the Hood Protector to prevent the screw plug from rotating. DO NOT OVERTIGHTEN SCREWS.
6. Check the Hood Protector is sitting center to the hood. Insert the small screws through the washer and Hood Protector into the metal clip. Fasten all the screws.
7. Carefully lower the hood and note where the wings of the Hood Protector sit over the fender. Open the hood and clean the noted areas with alcohol wipe. Wipe off any residue with a dry clean cloth. Adhere the abrasive resistant tape strips over the top of the fender.
TO REMOVE: Reverse the above procedure.
8. If necessary adjust engine bay bumpstops to increase the clearance between hood and Grille.

To Clean: Use mild detergent and water solution (Do **NOT** use solvents). Avoid the use of automatic "Brush Style" car washes. When closing the hood, do **NOT** pull on Hood Protector.



- Do not use power tools to install this product.
- No battery operated screw guns.
- The use of power tools during installation may void the product warranty.
- Do not overtighten.

