

INSTALLATION INSTRUCTIONS

INSTALLATION INSTRUCTIONS

- 1 • Position **Hood Product** centrally over hood.
• Note three holes corresponding to center slots in **Hood Product**.
- 2 • Insert plastic screw plugs into three holes previously noted.
- 3 • Install **Hood Product** and secure **Hood Product** to hood with screws provided.
- 4 • Clean with alcohol wipe provided, the areas on top and underside of hood corresponding to holes in outer edges of **Hood Product**.
• Adhere abrasive resistant tape strips to edge of hood corresponding to holes at either end of **Hood Product**.
• Ensure that only 1/2" of the tape folds under the lip.
- 5 • Position the spring section of clip over the abrasive resistant tape on the hood lip.
• **Note: It is essential that no part of the clip contacts the top surface of the hood.**
- 6 • Fasten the **Hood Product** wings to the clip with the phillips head screws and fiber washers provided.

● **Note:** On vehicles with limited hood to grill clearance it may be necessary to adjust hood bump stops. (Refer to owners manual).

To Remove: Reverse above procedure.

To Clean: Use mild detergent and water solution. (Do **NOT** use solvents).

Avoid the use of automatic "Brush Style" car washes.

When closing the hood, do **NOT** pull on **Hood Product**.

