

INSTALLATION INSTRUCTIONS



- Do not use power tools to install this product.
- No battery operated screw guns.
- The use of power tools during installation may void the product warranty.
- Do not overtighten.

INSTALLATION INSTRUCTIONS

1. Clean and open the hood. Trial fit the Hood Product centrally onto hood. Note rubber trim retaining plugs in the underside of hood corresponding to the slots in the Hood Product.
2. Remove the corresponding plugs from the rubber seal, then install the screw plugs into the vacant holes, as shown. Retain rubber seal plugs for possible future use.
3. Re-fit the Hood Product centrally, locating the Hood Product tags between the rubber seal and the hood. Fit the Hood Product tag slot over the collar of the screw plug.

IMPORTANT: Ensure the slot is located centrally over the screw plug collar.

4. Insert the self-tapping screw and washers into vacant holes in the rubber seal. Position the rubber seal over the Hood Product tags. Maintain thumb pressure against the underside of the Hood Product and rubber seal, insert the screws into the screw plugs. Ensure the Hood Product is centralised on hood then tighten screws.

IMPORTANT: Thumb pressure must be maintained to prevent the screw plug from rotating. DO NOT OVERTIGHTEN SCREWS.

To Clean: Use mild detergent and water solution. (Do **NOT** use solvents). Avoid the use of automatic "Brush Style" car washes. When closing the hood, do **NOT** pull on Hood Product.

