


INSTALLATION INSTRUCTIONS



- Do not use power tools to install this product.
- No Battery operated screws guns.
- The use of power tools during installation. may void the product warranty.
- Do not overtighten.

INSTALLATION INSTRUCTIONS

1. Position **Hood Product** centrally over hood. Note two holes corresponding to center slots in **Hood Product**.
2. Insert plastic screw plugs into two holes previously noted.
 - Ensure the screw plug boss heads are parallel to the hood edge.
3. Install **Hood Product** and secure **Hood Product** to hood with screws & washers provided.
4. Clean with alcohol wipe provided, the areas on top and underside of hood corresponding to holes in outer edges of **Hood Product**
 - Adhere abrasive resistant tape strips to edge of the hood corresponding to the holes at either end of **Hood Product**.
 - Ensure that only 1/2" of the tape folds under the hood lip.
5. Peel the backing of the rubber washer and adhere it, to the metal clip as shown.
6. Position the spring section of clip over the abrasive resistant tape on the hood lip.
 - **Note: It is essential that no part of the clip contacts the top surface of the hood.**
7. Fasten the **Hood Product** wings to the clip with the phillips head screws and fiber washers provided.

- **Note: On vehicles with limited hood to grill clearance it may be necessary to adjust hood bump stops.** (Refer to owners manual).

To Remove: Reverse above procedure.

To Clean: Use mild detergent and water solution. (Do **NOT** use solvents). Avoid the use of automatic "Brush Style" car washes.

When closing the hood, do **NOT** pull on **Hood Product**.

