

INSTALLATION INSTRUCTIONS



- Do not use power tools to install this product.
- No battery operated screw guns.
- The use of power tools during installation may void the product warranty.
- Do not overtighten.

To Clean: Use mild detergent and water solution. (Do **NOT** use solvents). Avoid the use of automatic "Brush Style" car washes. When closing the hood, do **NOT** pull on Hood Protector.

MADE IN AUSTRALIA

INSTALLATION INSTRUCTIONS

- 1• Clean and open the Hood. Trial fit Hood Protector centrally onto hood and note the six slots in the Hood Protector. Note the six square holes on the underside of hood that correspond with the Hood Protector slots. Mark these locations onto the hood with a non-permanent marker. Remove the Hood Protector.
- 2• Note the eight rubber seal retaining plugs in the underside of hood, as shown in Fig. 2. Carefully remove these retaining plugs. Be careful not to damage the retaining plugs, as they will need to be refitted at the end of installation of the Hood Protector.
- 3• Ease the rubber seal away from the hood and fit the six plastic screw plugs into the previously noted square holes corresponding to the Hood Protector slots.
- 4• Fit the Hood Protector between the rubber seal and the hood. Secure to the hood with the screws and washers provided, as shown in Fig. 4. **Do not over-tighten screws.** Refit the eight rubber retaining plugs to complete installation.

