




INSTALLATION INSTRUCTIONS



- Do not use power tools to install this product.
- No battery operated screw guns.
- The use of power tools during installation may void the product warranty.
- Do not overtighten.

INSTALLATION INSTRUCTIONS

- 1• Open & thoroughly clean the hood with a mild soap and water solution, then dry thoroughly. Trial fit the Hood Protector centrally onto hood. With a non-permanent marker, note and mark the positions of the holes in the Hood Protector onto hood. Also note the rubber trim retaining plugs that correspond to the holes in the Hood Protector tags. Remove Hood Protector.
- 2• Remove the four previously noted rubber trim retaining plugs using pliers if necessary. Insert screw plugs provided into the four vacant holes. Do not discard rubber trim retaining plugs.
- 3• Install the screw plugs.
- 4• Install Hood Protector onto hood ensuring that the Hood Protector tags fit between the hood and the rubber seal all the way along the hood edge. Ensure that the collar of the screw plugs locate into and parallel with the slots in the Hood Protector tags, as shown.
- 5• Secure Hood Protector to hood using the screws, spacers and silver washers provided. The correct sequence is screw plugs, Hood Protector, silver washers, spacers and screws. Stretch existing rubber trim over spacer to re-secure rubber trim in position.
- 6• Clean the noted areas under the wing clip locations with alcohol wipe provided. Wipe off any residue with a dry clean cloth. Adhere the abrasive resistant tape strips over the hood lip. Apply tape so approximately half of each strip is adhered to the top side and half is adhered to the underside of hood.
- 7• Slide wing clips over hood edge at the two previously noted outer positions. Secure Hood Protector to wing clips with small screws and black washers provided.
DO NOT OVER TIGHTEN SCREWS
IMPORTANT: Ensure that the clips are positioned over abrasive resistant tape and do not come in contact with any of the hood's paint work. Failure to do this may result in permanent paint damage.

To Clean: Use mild detergent and water solution (Do **NOT** use solvents). Avoid the use of automatic "Brush Style" car washes. When closing the hood, do **NOT** pull on Hood Protector.

