


INSTALLATION INSTRUCTIONS



NO POWER TOOLS

- Do not use power tools to install this product.
- No Battery operated screws guns.
- The use of power tools during installation may void the product warranty.
- Do not overtighten.

INSTALLATION INSTRUCTIONS

- 1 • Position **Hood Product** centrally over hood.
• Note four holes corresponding to center slots in **Hood Product**.
- 2 • Insert plastic screw plugs into four holes previously noted.
- 3 • Install **Hood Product** and secure **Hood Product** to hood with screws and washers provided.
- 4 • Clean with alcohol wipe provided, the areas on top and underside of hood corresponding to holes in outer edges of **Hood Product**.
• Adhere abrasive resistant tape strips to edge of hood corresponding to holes at either end of **Hood Product**.
• Ensure that only 1/2" of the tape folds under the lip.
- 5 • Position the spring section of clip over the abrasive resistant tape on the hood lip.
• Note: It is essential that no part of the clip contacts the top surface of the hood.
- 6 • Fasten the **Hood Product** wings to the clip with the philips head screws and fiber washers provided.

- Note: On vehicles with limited hood to grill clearance it may be necessary to adjust hood bump stops. (Refer to owners manual).

To Remove: Reverse above procedure.
To Clean: Use mild detergent and water solution. (Do NOT use solvents).
Avoid the use of automatic "Brush Style" car washes.
When closing the hood, do NOT pull on **Hood Product**.

