

INSTALLATION INSTRUCTIONS



- Do not use power tools to install this product.
- No battery operated screw guns.
- The use of power tools during installation avoid the product warranty.
- Do not overtighten.

INSTALLATION INSTRUCTIONS

1. Clean and open the hood. Trial fit the **Hood Product** centrally onto hood. Note the two (2) existing nuts that align with the products middle mounting holes, and the (2) holes in the hood corresponding to the two center slots in the **Hood Product**, also note the metal wing clip locations. Remove **Hood Product**.
2. Remove the (2) nuts previously noted. Install the screw plugs provided into the two (2) previously noted center holes in hood, as shown. Screw the double-headed screws into the screw plugs. If required, lock the screw plugs in place using a wrench. Ensure the double-headed screw is fully threaded into the screw plug. Ensure the wrench does not damage the hood paintwork.

Refit **Hood Product** centrally onto hood. Seat the slot of the **Hood Product** over the double-threaded screws. Attach the **Hood Protector** to the double-threaded screws with the knurl nuts and large black washers. Do not fully tighten yet. Ensure the **Hood Product** is centralised on hood then fully tighten screws. Re-fit previously removed (2) nuts ensuring product tag holes are centered over existing hood applique screws.

3. Clean the previously noted metal wing clip areas with alcohol wipe provided. Wipe off any residue with a dry clean cloth. Adhere the abrasive resistant tape strip over the hood lip. Apply tape so approximately half of each strip is adhered to the top side and half is adhered to the underside of hood.
4. Install the metal clips over the abrasive resistant tape strips at the previously marked locations. **Ensure the clips are fully seated over abrasive resistant tape. Ensure the clips do not come in contact with any of the hood's paint work. Failure to do this may result in permanent paint damage.** Finally, secure the **Hood Product** to the metal clips with the small screws and washers provided.

To Clean: Use mild detergent and water solution. (Do **NOT** use solvents). Avoid the use of automatic "Brush Style" car washers. When closing hood, do **NOT** pull on **Hood Product**.

