


INSTALLATION INSTRUCTIONS HOOD PRODUCT

INSTALLATION INSTRUCTION

- Do not use power tools to install this product.
- No Battery operated screws guns
- The use of power tools during installation, may void the product warranty.
- Do not overtighten.



1. Thoroughly clean & open the hood.
 - Remove the grille.
 - Position Hood Product centrally over hood.
 - Note the positions of the four tags.
 - Note & mark with a non-permanent marker the metal wing clip positions onto hood.
 2. Clean with alcohol wipe provided, the areas on top and underside of hood corresponding to holes in outer edges of Hood Product. Remove any residue with a dry clean cloth.
 - Adhere abrasive resistant tape strips to edge of hood corresponding to holes at either end of Hood Product.
 - Ensure that only 1/2" of the tape folds under the lip.
 3. Clean the face of the metal wing clip with the alcohol wipe provided. Remove any residue with a dry clean cloth. Peel the protective strip from the plate and adhere it to the face of metal wing clip, as shown.
 4. Position the spring section of clip over the abrasive resistant tape on the hood lip.

Note: It is essential that no part of the clip contacts the surface of the hood.
 5. Re-fit the Hood Product centrally and secure it to hood by re-fitting the removed grille.
 6. Secure the metal wing clips by using the screws and washers provided.
- **Note: On vehicles with limited hood to grille clearance it may be necessary to adjust hood bump stops.** (Refer to owners manual).
- To remove:** Reverse above procedure.
To clean: Use mild detergent and water solution. (Do NOT use solvents) Avoid the use of automatic "Brush Style" car washer.
 When closing the hood, do not pull on the Hood Product.

