

DIRECTIONS

1. Clean part thoroughly. Remove wax, grease, oil, buffing compounds, etc. with acetone or Eastwood's PRE Painting Prep #10041Z.
2. Use when can and surface temperature are between 70°– 90°F (21°– 32°C) and humidity is 50% or lower.
3. Shake can vigorously for at least 1 minute before and occasionally during use. Point opening of spray button toward part and hold can approximately 12 inches from surface. Use even, overlapping strokes. Apply several thin, even coats allowing 15 minutes dry time between each coat. For best protection, make sure you have complete coverage on the entire piece.
4. Allow surface to dry 24 hours before handling.
5. If clogging develops, turn spray button 1/4 turn. If clogging persists, remove and clean button with suitable solvent. Do not stick pin or sharp object into can opening.
6. Clean spray button for future use – turn can upside down and spray for 2 seconds.
7. Discard empty can according to Federal, State, and Local regulations. Do not place in home garbage compactor.

CONTAINS: Oxibismethane (CAS #115-10-6), n-Hexane (CAS #110-54-3), Xylene (CAS #1330-20-7), VM&P Naphtha (CAS #64742-89-8), Ligroine (CAS #8032-32-4), Liquefied Petroleum Gas (CAS #68476-85-7), and Acetone (CAS #67-64-1).

DANGER: CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE. Vapor Harmful. May affect the brain or nervous system causing dizziness, headache, or nausea. Causes eye, skin, nose, and throat irritation. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not store at temperatures above 120°F.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Vapors May Ignite Explosively. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening windows and doors to achieve cross-ventilation.

Use Only With Adequate Ventilation. Do not breathe dust, vapors, or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering,

headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Avoid contact with eyes, skin, and clothing.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water.

WARNING: This product contains a chemical known to the State of California to cause cancer.

KEEP OUT OF THE REACH OF CHILDREN

Clear Coating – Max MIR 1.77

Only in the Event of a Chemical Emergency Involving a Spill, Leak, Fire, or Exposure Call Toll Free Day or Night: Chemtrec 1-800-424-9300 (USA) (International Call Collect (202) 483-7616)

Manufactured for The Eastwood Company, 263 Shoemaker Rd. Pottstown, PA 19464, USA

USA: 1-800-345-1178 • Canada: 1-800-820-9042 • www.eastwood.com