

EASTWOOD RUST CONVERTER halts residual rust in its tracks and converts it into a black paintable polymeric coating. This coating is used as a primer on rusted metals and can be top coated with most paints. Once sealed with a top coat, the rust will not return or spread.

DIRECTIONS

Wire brush the loose rust from the surface. Clean the surface to remove grease and grime. Shake well before use. Hold can 8-12 inches from surface and spray a thin coat onto the surface. After the surface has dried, it will turn black. Then apply a second thin coat. Allow 4 - 8 hours to completely cure before painting while protecting it from rain or dew. For long lasting protection, seal with two coats of a high quality paint. Do not apply if the surface temperature is below 50°F or above 90°F. Do not apply over paint. Must be top coated or rust will return.

FIRST AID: IF IN EYES: Flush eyes and under eyelids with water for at least 15 minutes. Obtain medical attention.

IF ON SKIN: Flush skin with plenty of water for 15 minutes. Remove contaminated clothing, and launder before reuse. If irritation is persistent, contact a physician.

IF SWALLOWED: Contact physician or poison control center immediately. Rinse mouth with water and give affected person 1-2 glasses of water to dilute. Do not induce vomiting unless instructed by a physician or poison control center. Never give anything by mouth to an unconscious person.

IF INHALED: Remove person to fresh air. If symptoms develop, seek medical attention. If not breathing, give artificial respiration.

CONTAINS: Acetone 67-64-1, Isopropanol 67-63-0, Ethylene Glycol 107-21-1, Tannic Acid 1401-55-4, Propane/n-Butane 68476-86-8.

See MSDS for complete safety information.
CONTAINS NO OZONE DEPLETING CHEMICALS.

ANGER EXTREMELY FLAMMABLE

May cause burns and/or severe irritation to the eyes, skin, stomach, and respiratory tract. Prolonged or repeated contact may dry or defat the skin and lead to inflammation. Possible aspiration hazard – may cause inflammation of the lungs. May cause nausea, vomiting, pain and stomach upset (e.g. diarrhea). May affect the following organs upon prolonged or repeated overexposure: Liver, Kidneys, Nervous System, Heart, and/or Circulatory System. Keep away from heat, sparks, and flames. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F as container may burst. Avoid prolonged exposure to sunlight. Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec Toll Free Day or Night:
1-800-424-9300 International Call Collect: (202) 483-7616)

Manufactured for The Eastwood Company,
263 Shoemaker Road, Pottstown, PA 19464
USA: 1-800-345-1178 Canada: 1-800-820-9042
International: (610) 323-2200 www.eastwood.com
© Copyright 2011 Easthill Group, Inc. Made in USA



DO THE JOB RIGHT.

RUST CONVERTER



- Transforms Rust Into A Paintable Surface
- Eliminates Need For Sanding
- Seals and Prevents Rust

ANGER:

EXTREMELY FLAMMABLE. MAY CAUSE BURNS TO EYES, SKIN, AND RESPIRATORY TRACT. CONTENTS UNDER PRESSURE. KEEP OUT OF REACH OF CHILDREN.
Read Precautions On Rear Panel Before Use.

Net wt. 11 oz. / 312 grams

51483 Z