

Installation Instructions

Eibach Springs, Inc. • 264 Mariah Circle • Corona, California 92879-1751 • USA • Tech Support 800-222-8811 Ext 114



SPORTLINE # 4.6563

Infinity, G35, Coupe - 3.5L, 2003 - 2004

Kit Contents	Description	Part Number	Qty
	Front Spring	4.6563F	2
	Rear Spring	4.6563R	2
	Information Kit	EPACK	1
	Instructions	4.6563INST	1

NOTES: Read All Instructions Before Beginning Installation

- Only qualified mechanics experienced in the installation and removal of suspension components should perform this installation.
- Use of a hoist is highly recommended and will substantially reduce installation time.
- Never work on or under a vehicle unless it is properly supported by safety stands.
- **SPORTLINE** springs are marked with an **F**, for Front and **R**, for the Rear.
- **SPORTLINE** springs should be installed with the **Eibach** Logo right side up. All original stock spring isolators, dampers and tubing should be retained from the stock springs and used when installing the **SPORTLINE** Springs.
- After installation, it is always important to inspect and adjust the following if necessary:
 - Wheel alignment such as camber, caster & toe.
 - Tire and/or wheel fender clearance, when aftermarket tires and wheels are used.
 - Brake line clearance and attachments.
 - Brake anti-locking and anti-skid system sensors.

Tire Rotation: In order to increase the life of your tires, it is recommended to rotate your tires every 3,000 miles.

After installation, it will be necessary to perform a full vehicle alignment.

Additional Eibach Components Available For Your Car

Eibach Kits	Part Number	Description	Front	Rear
Anti-Roll-Kit	6365.320	Performance Tuned Handling	34MM Adj. Tubular	22MM Adj. Tubular

NO BUMP STOP TRIMMING REQUIRED ON THIS VEHICLE.

