

NOTE: THESE HEADLIGHTS ARE FOR OFF-ROAD USE ONLY.

**#42311 HEADLIGHT CONVERSION KIT INCLUDES:**

- 2 - #4231 H4 HEADLIGHTS
- 2 - H4 PHILIPS 55/60W BULBS
- 1 - #6307 H13-H4 CONVERSION HARNESS KIT

TOOLS REQ'D FOR INSTALLATION:

- 10mm Socket/Wrench
- T15 Torx Driver
- Flathead Screwdriver
- *Philips Screwdriver***

***Note: For earlier JK Models with Screw-type Retainer Tabs, it requires a Philips Screwdriver.*

INSTALLATION:

1. Pop open your Hood. Using a 10mm wrench, <Disconnect> the (-) Negative Terminal from the battery.
2. <Locate> the Turn Signal Wire Harness behind the grill through the wheel well and <Unlock> the connector by pulling out the red locking tab.
3. <Unplug> the connector by pressing and holding the release tab down while you pull it out.
4. Using the Flathead Screwdriver, <Remove> the (6) Plastic Retainer Tabs located along the top of the grill shroud by lifting the plastic pins and gently prying the tabs out. (For older model JKs, it will require using a Philips Screwdriver to unscrew the plastic lift pins.)
5. <Remove> the Jeep Wrangler Grille by firmly pulling on the lower part of the grille until the retainer clips break free of the chassis.

Tip: There are (6) Press-In Retainer Clips holding the Jeep Grille in place: (1) Located Above each turn signal (Left & Right) and (5) located along the bottom of the lower radiator support.
6. Using the T15 Torx Driver: <Remove> the (4) retaining ring screws holding the headlight assembly in place.
7. <Pull> headlight assembly out to expose the wire harness with connector. <Unplug> the headlight by unlocking the connector by sliding out the red locking tab, press and hold the release tab and disconnect the connector.
8. <Separate> the Retainer Ring from the OEM Headlight and discard the OEM Headlight.
9. Take the H13-H4 Harnesses Adapter (#6307) and <Connect> the Male H13 plug to the OEM Connector.
10. Take the KC H4 Headlight and <Connect> it to the H4 connector from the Harness Adapter (#6307).
11. The KC H4 Headlight is indexed to align with the Jeep Wrangler Headlight Housing. Make sure the indexed tabs are properly aligned before screwing the retainer ring back into place using the original T15 Retainer Ring Screws.
12. <Re-install> the Jeep Wrangler Grille by following Steps (1-7) in reverse order.

Enjoy your New H4 Headlights!