



54207

**07-08 GMC
SIERRA HD**

54207

**07-08 GMC
SIERRA HD**

2007 GMC SIERRA HD
MESH OVERLAY W/LOGO CUT OUT

Recommended Tools:

Phillips & Slotted Screwdrivers
5/16" & 10mm Socket & Ratchet

Parts List / Hardware:

- 1 Mesh Insert
- 9 6-32 Nylon Lock Nuts
- 5 2" J Hook Brackets
- 4 2 ½" J hook Brackets

Read and understand instructions before attempting installation

Step 1

Test fit the grille into the opening. Remove plastic rivets securing the radiator cover; on top of the grille. Now remove the four 10mm bolts along the top of the grille. The grille has six metal clips that clip into the core support (2); two behind the GMC logo and four along the bottom. Pull the grille forward; use a slotted screwdriver to release the clips and remove the grille. If a bumper grille is to be installed, install at this time.



Step 2

Place a longer J hooks on the outside edge studs; hand thread a nylon lock nut on each stud **(1)**. In the center of the grille; place the shorter J hooks on the studs. Hand thread a nylon lock nut on each stud. Center the grille over the factory shell. Make sure the hooks wrap around the rear edge of the factory grille. Tighten the hardware until the grille is held firmly in place.

Thank you for purchasing a T-Rex Billet Grille. 12/03/07