

2012 NISSAN VERSA

Upper Class Mesh Grille

Install time: 35 Mins.

TOOLS REQUIRED:

Socket Wrench
Plastic Prybar

PARTS LIST:

(1) Mesh Grille
(8) Fender Flatwashers
(8) 6/32 Nylon Lock Nuts
(4) Mounting Clips

PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION.

- Remove 5 Clips along the top of the Grille Shell. (Fig.1)
- Unclip 8 Clips along the Bottom of the Factory Grille to Remove.
- Remove 3 Clips to remove Plastic Cover that is on the right side of vehicle. (Fig. 2)
- Remove 5 Bolts from behind the Grille. (Fig. 3)
- Unclip the Grille along the bottom and remove. (Fig. 4)
- Unclip the Nissan Logo. (Fig. 5)
- Place the Mesh Grille through the Factory Opening. (Fig. 6)
- From behind the Grille, Place a Fender Flatwasher on the Threaded Studs and Thread with provided 6/32 Nylon Lock Nuts. (Fig. 7)
- Place the Nissan Logo through the Logo Plate and Insert the Mounting Clips from behind the Nissan Logo. (Fig. 8)

Installation Complete

