

66639
10-11 MAZDA
CX9



66639
10-11 MAZDA
CX9

10-11 MAZDA CX9

Custom Stainless Grille 2 Pc.

TOOLS REQUIRED:

8mm Socket and Ratchet
Flathead/Phillips Screwdriver

PARTS LIST

(4) 2" Flange Brackets
(4) 6/32 Nylon Lock Nuts
(1) Custom Stainless Grille 2 Pc.

PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS BEFORE

INSTALLATION. Auto makers offer varied models to each vehicle and occasionally manufacture more than one body style of the same model. To assure your part is correct; our tech department can be contacted at tech@trexbillet.com to verify fitment or assist with tech questions. All other inquiries can be directed to info@trexbillet.com. In the event you do not have internet access please call 1-800-287-5900.

Step 1

Loosen the radiator top cover. There are several plastic pop clips that you can pry up with a flathead screwdriver, two phillips screws and 2 plastic phillips pop clips (Fig 1). Pull the radiator cover up and forward, you can put a small 5-6" piece of styrofoam to hold it open. This will allow you to get your hand behind the grille to install the hardware.

Step 2

Take the stainless grille and insert it into the opening in the factory grille shell. (Fig 2)

Step 3

Reaching through the loose radiator cover, take the four 2" flange brackets and slide them over the four threaded studs on the backside of the stainless grilles with the tapered ends facing forward. Take the four 6/32" nylon lock nuts and install them over the flange brackets and tighten (Fig 3). Reinstall the hardware in the radiator cover. Installation complete.



Fig 1



Fig 2



Fig 3